Item Code: 100-080-WT-100













- X Cat6 24AWG Copper Cable
- X U/UTP No Overall Screening
- X No Conductor Screening
- X Outer sheath colour White
- X Reaction-to-fire class according to EN 13501-6: Dca
- X Smoke development class according to EN 13501-6:
- X CIBSE TM65 Embodied Carbon: 24.641 kg CO26

#### **Product Overview**

Excel solid Cat6 ethernet cable U/UTP 24AWG LSOH CPR Dca manufactured and tested to the TIA/EIA 568-B.2-1, EN50173-1 and ISO/IEC 11801 Cat 6 specifications, 100m, 305m or 500m. Each cable consists of 8 colour coded solid copper conductors twisted together to form four pairs.

These are then formed around a central X-shaped polyethylene centre with the whole cable produced in a LSOH sheath.

### **Product Specifications**


Feature	Values
Conductor surface	Bare
AWG size	24
Conductor category	Class 1 = solid
Total number of cores	8
Stranding element	Pairs
Specification core insulation	Polyethylene (PE)
Core identification	Colour

Item Code: 100-080-WT-100



Overall screening	None
Conductor screening	None
Outer sheath material	Copolymer, thermoplastic (LS0H)
Outer sheath colour	White
Flame retardant according to IEC 60332-1-2	yes
Reaction-to-fire class according to EN 13501-6	Dca
Smoke development class according to EN 13501-6	s2
Euro class flaming droplets/particles according to EN 13501-6	d2
Euro class acidity according to EN 13501-6	al
Outer diameter approx.	6.1 mm
Installation Temperature Range	-1060 °C
Operating Temperature Range	-2075 °C
Category	6
NVP value	69 %

## **Cross-section diagram**



### core:

P1: White/Blue

P2: White/Orange

P3: White/Green

P4: White/Brown

Item Code: 100-080-WT-100



## **Cable specifications**

Features	Values
Dielectric strength	2.5 kV for 2s
Maximum pulling load	60 N/6.1 KgF
MBR during installation	8x cable OD
MBR installed	4x cable OD

#### **Standards**

Applicable standard	Subject
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
IEC 61156-5:2020	Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Horizontal floor wiring - Sectional specification
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
EN 50173-2:2018	Information technology. Generic cabling systems - Office premises
BS EN 50288-3-1:2013	Multi-element metallic cables used in analogue and digital communication and control. Sectional specification for unscreened cables characterised up to 250 MHz
EN 50399:2011+A1:2016	Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results
IEC 60332-1-2:2004 + A12:2020	Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame
ANSI/TIA 568-D:2015	Balanced Twisted-Pair Telecommunications Cabling and Components Standards
IEC 60754-2:2014	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity
IEC 61034-2:2005+A2:2020	Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements
EN 50575:2014 + A1:2016	Power, control and communication cables — Cables for

Item Code: 100-080-WT-100



	general applications in construction works subject to reaction to fire requirements
RoHS-II/-III (2011/65/EU & 2015/863): 2023	Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).
WFD: 2023	Compliant to Waste Framework Directive
SCIP: 2023	Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
POPs (EU) No 2019/1021	EU Regulation for the restriction of Persistent Organic Pollutants.

### **Part Number Table**

Part Number	Description
100-080	Excel Solid Cat6 Cable U/UTP 24AWG LSOH CPR Dca 305 m Box Violet
100-080-WT	Excel Solid Cat6 Cable U/UTP 24AWG LSOH CPR Dca 305 m Box White
100-080-WT-100	Excel Solid Cat6 Cable U/UTP 24AWG LSOH CPR Dca 100 m Box White

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.