
Excel Patch Cable Cat5e U/UTP PVC 305 m Box for Patch Leads Yellow

Part Code: 100-091-305M

sales@excel-networking.com
excel-networking.com

CIBSE TM65 Embodied Carbon: 55.177 kg CO2e



Main Features

- Cat5e Patch Lead Cable
- No Conductor Screening
- 24 AWG size conductors
- U/UTP No Overall Screening
- Outer sheath colour Yellow
- Specification core insulation PE

Product Overview

Excel Cat5e ethernet patch lead cable U/UTP PVC are manufactured and tested to ISO 11801, EN 50173 and ANSI/TIA□568□C Cat 5e specifications, 305m boxes. Each cable consists of 8 colour coded stranded copper conductors twisted together to form four pairs. The whole cable is produced in a PVC sheath and is highly flexible and easy to use.

The cable is available in many colours allowing bespoke patch leads to be made using appropriate plugs.

Product Specifications

This data sheet was generated at 10:20am 11th November 2026 and is subject to change at any time.

Excel Patch Cable Cat5e U/UTP PVC 305 m Box for Patch Leads Yellow


Part Code: 100-091-305M

sales@excel-networking.com
excel-networking.com

Feature	Values
Cable type	**U/UTP**
Conductor material	**Copper**
Conductor surface	**Bare**
AWG size	**24**
Conductor category	**Class 2 = stranded**
Total number of cores	**8**
Stranding element	**Pairs**
Specification core insulation	**Polyethylene (PE)**
Core identification	**Colour**
Overall screening	**None**
Conductor screening	**None**
Outer sheath material	**Polyvinyl chloride (PVC)**
Outer sheath colour	**Yellow**
Flame retardant according to IEC 60332-1-2	**yes**
Outer diameter approx.	**5.3 mm**
Category	**5E**

This data sheet was generated at 10:20am 11th November 2026 and is subject to change at any time.

Cross-section diagram



Cable specifications

Features	Values
Maximum Pulling Load	**60N/6.1KgF**
MBR during installation	**8x cable OD**
MBR installed	**4x cable OD**
Ripcord	**Nylon**

Standards

Applicable standard	Subject
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
IEC 61156-5:2020	Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz -

This data sheet was generated at 10:20am 11th November 2026 and is subject to change at any time.

	Horizontal floor wiring - Sectional specification
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
EN 50173-2:2018	Information technology. Generic cabling systems - Office premises
BS EN 50288-3-1:2013	Multi-element metallic cables used in analogue and digital communication and control. Sectional specification for unscreened cables characterised up to 250 MHz
EN 50399:2011+A1:2016	Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results
IEC 60332-1-2:2004 + A12:2020	Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame
ANSI/TIA 568-D:2015	Balanced Twisted-Pair Telecommunications Cabling and Components Standards
IEC 60754-2:2014	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity
IEC 61034-2:2005+A2:2020	Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements
EN 50575:2014 + A1:2016	Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances

This data sheet was generated at 10:20am 11th November 2026 and is subject to change at any time.

	of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
UK SI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

Part Code Table

Part Code	Description
100-081-305M	**Excel Patch Cable Cat5e U/UTP PVC 305 m Box for Patch Leads Grey**
100-082-305M	**Excel Patch Cable Cat5e U/UTP PVC 305 m Box for Patch Leads Blue**
100-083-305M	**Excel Patch Cable Cat5e U/UTP PVC 305 m Box for Patch Leads Green**
100-084-305M	**Excel Patch Cable Cat5e U/UTP PVC 305 m Box for Patch Leads Black**
100-089-305M	**Excel Patch Cable Cat5e U/UTP PVC 305 m Box for Patch Leads White**
100-091-305M	**Excel Patch Cable Cat5e U/UTP PVC 305 m Box for Patch Leads Yellow**

This data sheet was generated at 10:20am 11th November 2026 and is subject to change at any time.