Item Code: 100-100











- X Cat6 external grade cable for external use
- X No conductor screening
- X Outer sheath colour black
- X Reaction-to-fire class according to EN 13501-6: Fca
- X 23 AWG size conductors
- X UV Exposure tested in accordance with ASTM G154 & G155
- X CIBSE TM65 Embodied Carbon: 64.808 kg CO2e

Product Overview

Excel Cat6 ethernet cable U/UTP PE external Grade Fca manufactured and tested to the TIA/EIA 568-B.2-1, EN50173-1 and ISO/ IEC 11801 Cat6 specifications, sold in 305 m boxes. Each cable consists of 8 colour coded solid copper conductors twisted together to form four pairs.

These are then formed around a central X-shaped polyethylene centre with the whole cable produced in a PE sheath.

Product Specifications


| Feature | Values |
|-------------------------------|-------------------|
| Conductor surface | Bare |
| AWG size | 23 |
| Conductor category | Class $1 = solid$ |
| Total number of cores | 8 |
| Stranding element | Pairs |
| Specification core insulation | Polyethylene (PE) |
| Core identification | Colour |

Item Code: 100-100



| Overall screening | None |
|--|----------|
| Conductor screening | None |
| Outer sheath material | PE |
| Outer sheath colour | Black |
| Flame retardant according to IEC 60332-1-2 | yes |
| Reaction-to-fire class according to EN 13501-6 | Fca |
| Outer diameter approx. | 6.3 mm |
| Operating Temperature Range | -1075 °C |
| Category | 6 |
| NVP value | 69 % |

Cross-section diagram



Cable specifications

| Features | Values |
|-------------------------|---------------|
| Dielectric strength | 2.5 kV for 2s |
| Maximum pulling load | 60 N/6.1 KgF |
| MBR during installation | 8x cable OD |
| MBR installed | 4x cable OD |

Item Code: 100-100



Standards

| Applicable standard | Subject |
|--|--|
| ISO/IEC 11801-1:2017 | Information technology - Generic cabling for customer premises: Part 1 General Requirements |
| IEC 61156-5:2020 | Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Horizontal floor wiring - Sectional specification |
| EN 50173-1:2018 | Information technology. Generic cabling systems - General requirements |
| EN 50173-2:2018 | Information technology. Generic cabling systems - Office premises |
| BS EN 50288-3-1:2013 | Multi-element metallic cables used in analogue and digital communication and control. Sectional specification for unscreened cables characterised up to 250 MHz |
| EN 50399:2011+A1:2016 | Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results |
| IEC 60332-1-2:2004 + A12:2020 | Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame |
| ANSI/TIA 568-D:2015 | Balanced Twisted-Pair Telecommunications Cabling and Components Standards |
| IEC 60754-2:2014 | Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity |
| IEC 61034-2:2005+A2:2020 | Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements |
| EN 50575:2014 + A1:2016 | Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements |
| RoHS-II/-III (2011/65/EU & 2015/863): 2023 | Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III). |
| WFD: 2023 | Compliant to Waste Framework Directive |
| SCIP: 2023 | Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products) |
| POPs (EU) No 2019/1021 | EU Regulation for the restriction of Persistent Organic Pollutants. |

Item Code: 100-100



Part Number Table

| Part Number | Description |
|-------------|---|
| 100-100 | Excel Solid Cat6 Cable U/UTP PE External Grade Fca 305 m Box Black |
| 100-100-500 | Excel Solid Cat6 Cable U/UTP PE External Grade Fca 500 m Reel Black |

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.