Item Code: 100-188-WT









- X High quality housing with metallic back sized for specific Nordic market
- X Toolless termination design
- X Low profile design just 28mm overall depth
- X Supports 10 Gigabit Ethernet application
- X Choice of colours
- X 3rd Party ISO11801 2nd Edition verification
- X CIBSE TM65 Embodied Carbon: 0.396 kg CO2e

### **Product Overview**

100-188-WT Excel Cat6a UTP Unscreened Low Profile Keystone Jack Toolless White, available as part of our range of excel cat6a keystone jacks for RJ45 network connections.

This Low Profile Cat6a Keystone Jack is a reduced size toolless termination RJ45 socket which allows for multiple cable entry directions when this jack is mounted in a standard depth back box. This supports options including flush shutters at the outlet and angled shutters often used with keystone jacks. Designed to fit into Nordic territories face plates that have larger apertures than standard faceplates.

### **Product Specifications**

Feature	Values	
Model	Jack	
Type of connector	RJ45 8(8)	
Shielded	no	
Category	6A (IEC)	
Requires termination tool	no	
Suitable for round cable	yes	

Item Code: 100-188-WT



Suitable for flat cable	no
Suitable for solid core	yes
Colour	White
AWG-range	2226


## **Additional specifications**


Features	Values
Width	16.2mm
Depth	28.3mm
Hight	21.5mm
Housing	Polymer and Die cast Zinc-alloy
RJ45 Contacts	Nickel plated phosphor bronze alloy with 50 micro-inch Gold plating
IDC Contacts	Tin plated phosphor bronze alloy
RJ45 Life	Minimum 750 insertions
Storage temperature	-40 to +70°C
Operating temperature	-10 to +60°C

Item Code: 100-188-WT



## **Product drawing**





#### **Included accessories**

Accessories	Singles	24-packs
Nylon cable tie	1	24
Wiring cap	1	24

### **Standards**

Applicable standard	Detail
RoHS-II/-III (2011/65/EU & 2015/863): 2023	Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
ANSI/TIA 568-2.D	Balanced Twisted-Pair Telecommunications Cabling and Components Standards

Item Code: 100-188-WT



UL-94-V-0	Burning stops within $10$ seconds after two applications of ten seconds each of a flame to a test bar. NO flaming drips are allowed.
WFD: 2023	Compliant to Waste Framework Directive
SCIP: 2023	Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
POPs (EU) No 2019/1021	EU Regulation for the restriction of Persistent Organic Pollutants.

#### **Part Number Table**

Part Number	Description
100-188-BK	Excel Cat6A UTP Unscreened Low Profile Keystone Jack Toolless Black Nordic Market
100-188-BK-24	Excel Cat6A UTP Unscreened Low Profile Keystone Jack Toolless Black (Box 24)
100-188-WT	Excel Cat6A UTP Unscreened Low Profile Keystone Jack Toolless White Nordic Market
100-188-WT-24	Excel Cat6A UTP Unscreened Low Profile Keystone Jack Toolless White Nordic Market (Box 24)

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.