| Excel Cat6 UTP Unscreened Keystone Jack Toolless<br>White (Box 24) |  |
|--|--|
| Item Code: 100-211-24  |  |









| $oldsymbol{\lambda}$ IDC point at 180 degrees to jack |
|---|
| $oldsymbol{\lambda}$ Toolless termination design      |
| $oldsymbol{\lambda}$ Delta 3rd party verified         |
| $oldsymbol{	imes}$ UL94V-0 fire retardant plastic     |
| $oldsymbol{	imes}$ Supports Gigabit Ethernet          |
| $oldsymbol{	imes}$ ISO, EN & TIA compliant            |
| X CIBSE TM65 Embodied Carbon: 6.349 kg CO2e           |

### **Product Overview**

Excel Cat6 UTP Unscreened Keystone Jack Toolless White Box 24, available as part of our range of excel Cat6 keystone jacks for RJ45 network connections.

A toolless termination RJ45 socket suitable for mounting in a range of housings from patch panels, faceplates and shutters to sub-floor boxes and distribution enclosures. The socket is manufactured in a high quality ABS housing, with butterfly style Toolless IDC termination points.

Once the pairs are arranged in the cable management cap and trimmed it is a simple case of closing the ?butterfly? together to complete the termination.

Third party verification by Delta assures this high performance jack exceeds the requirements of the ISO, EN & TIA component standards.

### **Product Specifications**

| Feature                   | Values    |
|---------------------------|-----------|
| Model                     | Jack      |
| Type of connector         | RJ45 8(8) |
| Shielded                  | no        |
| Category                  | 6         |
| Requires termination tool | no        |




| Suitable for round cable | yes   |
|--------------------------|-------|
| Suitable for flat cable  | no    |
| Suitable for solid core  | yes   |
| Colour                   | White |
| AWG-range                | 2226  |


## Additional specifications

| Features             | Values   |
|----------------------|--|
| Width                | 17mm   |
| Depth                | 35.1mm   |
| Height               | 25.20mm  |
| Housing              | ABS High-Impact  |
| RJ45 Contacts        | Nickel plated phosphor bronze alloy with 50 micro-inch<br>Gold plating |
| IDC Contacts         | Tin plated phosphor bronze alloy                                       |
| RJ45 Life            | Minimum 750 insertions   |
| Storage temprature   | -40 to +70°C   |
| Operating temprature | -10 to +60°C   |



## **Product drawing**





## **Included accessories**

| Accessories     | Singles | 24-packs |
|-----------------|---------|----------|
| Nylon cable tie | 1       | 24       |
| Wiring cap      | 1       | 24       |

### Standards

| Applicable standard                        | Detail  |
|--|---|
| RoHS-II/-III (2011/65/EU & 2015/863): 2023 | Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III). |
| ISO/IEC 11801-1:2017                       | Information technology - Generic cabling for customer premises: Part 1 General Requirements   |
| EN 50173-1:2018                            | Information technology. Generic cabling systems -<br>General requirements   |
| ANSI/TIA 568-2.D                           | Balanced Twisted-Pair Telecommunications Cabling and<br>Components Standards  |
| UL-94-V-0                                  | Burning stops within 10 seconds after two applications of   |



|                        | ten seconds each of a flame to a test bar. NO flaming drips are allowed.                                |
|------------------------|---|
| WFD: 2023              | Compliant to Waste Framework Directive  |
| SCIP: 2023             | Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products) |
| POPs (EU) No 2019/1021 | EU Regulation for the restriction of Persistent Organic<br>Pollutants.                                  |

### **Part Number Table**

| Part Number | Description   |
|-------------|---|
| 100-211     | Excel Cat6 UTP Unscreened Keystone Jack Toolless White          |
| 100-211-24  | Excel Cat6 UTP Unscreened Keystone Jack Toolless White (Box 24) |
| 100-212     | Excel Cat6 UTP Unscreened Keystone Jack Toolless Black          |
| 100-212-24  | Excel Cat6 UTP Unscreened Keystone Jack Toolless Black (Box 24) |

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.