Excel Cat6A FTP Screened 6 Port ExpressNet Module IDC Punch down Silver

Part Code: 100-237

sales@excel-networking.com
excel-networking.com

CIBSE TM65 Embodied Carbon: 4.062 kg CO2e



Main Features

/ Housing for six connections compatible with Excel ExpressNet panel

/ Supports 10 Gigabit Ethernet application

/ 3rd party ISO11801 2nd edition verification

/ Cables entering module are individually secured

/ 25 year system warranty

/ CIBSE TM65 Embodied Carbon: 4.062 kg CO2e

Product Overview

Excel Cat6a FTP Screened 6 Port ExpressNet Module IDC Punch down Silver, offers a flexible and quick way to terminate and install structured cabling. Manufactured from high impact flame retardant plastic, the modules use IDC punch downs for the termination of the copper cables. The incoming cables are secured in place with cable ties resulting in a fully covered termination. The modules are easily fitted and removed from the rear of the patch panel by activating release latches.

Product Specifications

This data sheet was generated at 5:55am 17th November 2026 and is subject to change at any time.

Excel Cat6A FTP Screened 6 Port ExpressNet Module IDC Punch down Silver


Part Code: 100-237

sales@excel-networking.com
excel-networking.com

Feature	Values
Model	**Jack**
Type of connector	**RJ45 8(8)**
Shielded	**yes**
Category	**6A (IEC)**
Connection type	**LSA**
Requires termination tool	**Punch-down**
Suitable for round cable	**yes**
Suitable for solid cores	**yes**
Colour	**Silver**

This data sheet was generated at 5:55am 17th November 2026 and is subject to change at any time.

Product drawing



Additional specifications

Features	Values
Width	**92.95mm**
Depth	**90mm**
Height	**18mm**
Housing	**Die cast Zinc-alloy**
RJ45 Contacts	**Nickel plated phosphor bronze alloy with 50 micro-inch Gold plating**
IDC Contacts	**Tin plated phosphor bronze alloy**
RJ45 Life	**Minimum 750 insertions**

This data sheet was generated at 5:55am 17th November 2026 and is subject to change at any time.

Insulation resistance	**500 MΩ**
Dielectric withstanding voltage	**1000 V AC**
Storage temprature	**-40°C to +70°C**
Operating temprature	**-10°C to +60°C**

Standards

Applicable standard	Detail
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
ANSI/TIA 568-2.D	Balanced Twisted-Pair Telecommunications Cabling and Components Standards
UL-94-V-0	Burning stops within 10 seconds after two applications of ten seconds each of a fl ame to a test bar. No flaming drips are allowed.
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the

This data sheet was generated at 5:55am 17th November 2026 and is subject to change at any time.

	Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
UK SI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

Part Code Table

Part Code	Description
100-237	**Excel Cat6A FTP Screened 6 Port ExpressNet Module IDC Punch down Silver**

This data sheet was generated at 5:55am 17th November 2026 and is subject to change at any time.