

Excel Cat6 Solid Patch Lead U/UTP Unshielded LSOH Blade Booted 15 m Violet

Part Code: 100-368

sales@excel-networking.com
excel-networking.com



Main Features

- / Solid core cable - ideal for switch links
- / Backwards compatible
- / T568B wiring
- / Category 6
- / Independently verified
- / Blade style 'slimline' moulded strain relief boot with clip protector

Product Overview

Excel Category 6 U/UTP Solid Core patch leads are manufactured and tested to ISO 11801, EN 50173 & TIA/EIA 568 requirements for patch cord assemblies and provide optimum performance levels for structured cabling installations.

Product Specifications

Feature	Values
---------	--------

Excel Cat6 Solid Patch Lead U/UTP Unshielded LSOH Blade Booted 15 m Violet

Part Code: 100-368

sales@excel-networking.com
excel-networking.com

Cable type	U/UTP
Category	6
Length	15 m
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
Outer sheath colour	Violet
Strain relief boot	Moulded-on
Lockable	no
Strain relief boot colour	Violet
Flame retardant version	yes
Cable construction	1x4
AWG-size	23
Pin assignment	1:1

Excel Cat6 Solid Patch Lead U/UTP Unshielded LSOH Blade Booted 15 m Violet

Part Code: 100-368

sales@excel-networking.com
excel-networking.com

Product drawing



Standards

Applicable standard	Detail
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
EN 50173-1:2011	Information technology. Generic cabling systems - General requirements
ANSI/TIA 568-2.D	Balanced Twisted-Pair Telecommunications Cabling and Components Standards
IEC 61156-5:2009+AMD1:2012 CSV	Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Horizontal floor wiring - Sectional specification
IEC 60332-1-2:2004	Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame
EN 50575:2014 + A1:2016	Power, control and communication cables — Cables for

Excel Cat6 Solid Patch Lead U/UTP Unshielded LSOH Blade Booted 15 m Violet

Part Code: 100-368

sales@excel-networking.com
excel-networking.com

general applications in construction works subject to reaction to fire requirements

EN 50399:2011+A1:2016

Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results

IEC 61034-2:2005+A1:2013

Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements

Part Code Table

Part Code	Description
100-367	Excel Cat6 Solid Patch Lead U/UTP Unshielded LSOH Blade Booted 10 m Violet
100-368	Excel Cat6 Solid Patch Lead U/UTP Unshielded LSOH Blade Booted 15 m Violet
100-369	Excel Cat6 Solid Patch Lead U/UTP Unshielded LSOH Blade Booted 20 m Violet
100-370	Excel Cat6 Solid Patch Lead U/UTP Unshielded LSOH Blade Booted 30 m Violet
190-367	Excel Cat6 Solid Patch Lead U/UTP Unshielded LSOH B2ca Blade Booted 10m Violet
190-368	Excel Cat6 Solid Patch Lead U/UTP Unshielded LSOH B2ca Blade Booted 15m Violet
190-369	Excel Cat6 Solid Patch Lead U/UTP Unshielded LSOH B2ca Blade Booted 20m Violet
190-370	Excel Cat6 Solid Patch Lead U/UTP Unshielded LSOH B2ca Blade Booted 30m Violet