



- ☒ Suitable for high density switches and panels
- ☒ Reduced outside diameter - 3.8mm OD
- ☒ Category 6
- ☒ Backward compatible
- ☒ Independently verified
- ☒ Choice of colours
- ☒ T568B wiring

Product Overview

Excel Category 6 U/UTP Mini patch leads are manufactured and tested to ISO 11801, EN 50173 & TIA/EIA 568-C-2 requirements for patch cord assemblies and provide optimum performance levels for structured cabling installations. Each cable has a low smoke zero halogen outer sheath as standard and the small 3.8mm outside diameter makes them ideal for data centre and high density environments where there are high density patching fields and blade server/switch chassis deployments, allowing for maximum use of valuable rack space.

Product Specifications

Feature	Values
Cable type	U/UTP
Category	6
Length	0.75 m
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
Outer sheath colour	Blue
Strain relief boot	Moulded-on
Lockable	no

Strain relief boot colour	Blue
Flame retardant version	yes
Cable construction	1x4
AWG-size	28
Pin assignment	1:1

Part Number Table

Part Number	Description
100-689	Excel Cat6 Mini P/Lead U/UTP LSOH 0.75 m Blue

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.

excel
without compromise.