

Excel Cat6 Lockable Patch Lead U/UTP Unshielded LSOH Blade Booted 5 m Grey

Item Code: 101-108



- Secure, prevents unwanted disconnection
- Keys sold separately
- Category 6
- Backwards compatible
- Independently verified
- T568B wiring
- LSOH outer sheath

Product Overview

Excel Category 6 U/UTP Lockable patch leads are manufactured and tested to ISO 11801, EN 50173 & TIA/EIA 568 requirements for patch cord assemblies and provide optimum performance levels for structured cabling installations.

Excel Category 6 U/UTP Lockable patch leads provide added security, preventing unwanted disconnection on secure or sensitive circuits. Disconnection can only be achieved by using the key which is supplied separately to the Patch Leads.

Product Specifications

Feature	Values
Cable type	U/UTP
Category	6
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
Outer sheath colour	Grey
Strain relief boot	Moulded-on
Lockable	yes
Strain relief boot colour	Grey
Flame retardant version	yes


Excel Cat6 Lockable Patch Lead U/UTP Unshielded
LSOH Blade Booted 5 m Grey

Item Code: 101-108



Cable construction	1x4
AWG-size	24
Pin assignment	1:1

Product drawing



Standards

Applicable standard	Detail
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
ANSI/TIA 568-2.D	Balanced Twisted-Pair Telecommunications Cabling and Components Standards
IEC 61156-5:2009+AMD1:2012 CSV	Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Horizontal floor wiring - Sectional specification
IEC 60332-1-2:2004	Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame
IEC 61034-2:2005+A1:2013	Measurement of smoke density of cables burning under defined conditions - Part 2: Test procedure and requirements

Excel Cat6 Lockable Patch Lead U/UTP Unshielded LSOH Blade Booted 5 m Grey

Item Code: 101-108



RoHS-II/-III (2011/65/EU & 2015/863): 2023

Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).

WFD: 2023

Compliant to Waste Framework Directive

SCIP: 2023

Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)

POPs (EU) No 2019/1021

EU Regulation for the restriction of Persistent Organic Pollutants.

Part Number Table

Part Number	Description
101-100	Excel Cat6 Lockable Patch Lead U/UTP Unshielded LSOH Blade Booted 0.5 m Grey
101-102	Excel Cat6 Lockable Patch Lead U/UTP Unshielded LSOH Blade Booted 1 m Grey
101-104	Excel Cat6 Lockable Patch Lead U/UTP Unshielded LSOH Blade Booted 2 m Grey
101-106	Excel Cat6 Lockable Patch Lead U/UTP Unshielded LSOH Blade Booted 3 m Grey
101-108	Excel Cat6 Lockable Patch Lead U/UTP Unshielded LSOH Blade Booted 5 m Grey

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.