
Excel Cat6A 28AWG Patch Lead U/FTP Shielded LSOH 3 m Grey

Part Code: 103-203

sales@excel-networking.com
excel-networking.com

CIBSE TM65 Embodied Carbon: 0.939 kg CO2e



Main Features

- / 28AWG reduced diameter
- / LSOH outer sheath
- / Plastic free packaging
- / Moulded strain relief boot
- / Individual foil screenover each pair
- / CIBSE TM65 Embodied Carbon: 0.939 kg CO2e

Product Overview

Excel Category 6A (Augmented Category 6) patch leads take the performance capabilities of copper infrastructure to new levels. Designed to the current ISO and EIA/TIA standards for Class EA Augmented Category 6A performance these products are intended to deliver reliable, high network performance including support of emerging applications such as 10GBase-T, 10 Gigabit Ethernet.

Each Excel Category 6A patch lead consists of 4 twisted pairs of 28AWG stranded copper wires, an aluminium/polyester foil tape provides an individual screen for each pair. These pairs are then cabled together, with different lay lengths to ensure optimum performance.

Staggered pin RJ45 Screened plugs, terminate the cable, and each lead is fitted with colour coded moulded boots.

This data sheet was generated at 6:35pm 28th November 2026 and is subject to change at any time.

sales@excel-networking.com
excel-networking.com


Product Specifications

Feature	Values
Cable type	**U/FTP**
Category	**6A (IEC)**
Length	**3 m**
Type of connector connection 1	**RJ45 8(8)**
Type of connector connection 2	**RJ45 8(8)**
Outer sheath colour	**Grey**
Strain relief boot	**Moulded-on**
Lockable	**no**
Strain relief boot colour	**Grey**
Flame retardant version	**yes**
Cable construction	**1x4**
AWG-size	**28**
Pin assignment	**1:1**

This data sheet was generated at 6:35pm 28th November 2026 and is subject to change at any time.

sales@excel-networking.com
excel-networking.com

Product drawing



Standards

Applicable standard	Detail
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
ANSI/TIA 568-2.D	Balanced Twisted-Pair Telecommunications Cabling and Components Standards
IEC 61156-5:2009+AMD1:2012 CSV	Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Horizontal floor wiring - Sectional specification
IEC 60332-1-2:2004	Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame

This data sheet was generated at 6:35pm 28th November 2026 and is subject to change at any time.

IEC 61034-2:2005+A1:2013	Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
UK SI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

Part Code Table

Part Code	Description
103-200-10	**Excel Cat6A 28AWG Patch Lead U/FTP Shielded LSOH 0.5 m Grey (10-Pack)**
103-201	**Excel Cat6A 28AWG Patch Lead U/FTP Shielded LSOH 1 m Grey**
103-202	**Excel Cat6A 28AWG Patch Lead U/FTP Shielded LSOH 2 m Grey**
103-203	**Excel Cat6A 28AWG Patch Lead U/FTP Shielded LSOH 3 m Grey**

This data sheet was generated at 6:35pm 28th November 2026 and is subject to change at any time.

sales@excel-networking.com
excel-networking.com

103-205	**Excel Cat6A 28AWG Patch Lead U/FTP Shielded LSOH 5 m Grey**
103-210	**Excel Cat6A 28AWG Patch Lead U/FTP Shielded LSOH 10 m Grey**

This data sheet was generated at 6:35pm 28th November 2026 and is subject to change at any time.