

Excel Cat6A Solid Patch Lead U/FTP Shielded LS0H Cca Blade Booted 20m Blue

Item Code: 170-123



- ✕ Category 6A compliant
- ✕ Solid core cable
- ✕ For switch/harness links and CP cables
- ✕ LS0H Outer Sheath
- ✕ Euroclass Cca-s1a-d1-a1

Product Overview

Excel Category 6A solid core (F/FTP) screened Harness/Switch Link Leads are constructed from 190-996 Excel solid Cat6A cable F/FTP LS0H screened cable Ice Blue (horizontal cable).

Each of these leads allows the construction of two Switch/Harness Links or Consolidation Point (CP) Cables. The lead is manufactured with a high performance screened RJ-45 plug on each end permitting the lead to be cut into two at the required lengths.

Slimline blade strain relief boots are fitted to protect the latch and allow connection to the highest density equipment. Using the same cable as the horizontal elements of the channel assures performance and does not "use up" the stranded patch lead allowance.

These leads are for the creation of Switch/Harness Links and CP cables. They are not for use as a replacement for patch leads.

Product Specifications

Feature	Values
Cable type	U/FTP
Category	6A (IEC)
Length	20 m
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
Outer sheath colour	Blue
Strain relief boot	Push-on
Lockable	no
Strain relief boot colour	Blue
Flame retardant version	yes

Excel Cat6A Solid Patch Lead U/FTP Shielded LS0H Cca Blade Booted 20m Blue

Item Code: 170-123



Cable construction 1x4

AWG-size 23

Pin assignment 1:1

Standards

Applicable standard	Detail
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
ANSI/TIA 568-2.D	Balanced Twisted-Pair Telecommunications Cabling and Components Standards
IEC 61156-5:2009+AMD1:2012 CSV	Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Horizontal floor wiring - Sectional specification
IEC 60332-1-2:2004	Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame
EN 50575:2014 + A1:2016	Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements
EN 50399:2011+A1:2016	Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results
IEC 61034-2:2005+A1:2013	Measurement of smoke density of cables burning under defined conditions - Part 2: Test procedure and requirements

Part Number Table

Part Number	Description
100-124	Excel Cat6A Solid Patch Lead U/FTP Shielded LS0H Blade Booted 30m Ice Blue
170-123	Excel Cat6A Solid Patch Lead U/FTP Shielded LS0H Cca Blade Booted 20m Blue
170-124	Excel Category 6A Solid Patch Lead U/FTP Shielded LS0H Cca Blade Booted 30m - Blue
170-143	Excel Cat6A Solid Patch Lead U/FTP Shielded LS0H Cca Blade Booted 5m Ice

Excel Cat6A Solid Patch Lead U/FTP Shielded LS0H
Cca Blade Booted 20m Blue

Item Code: 170-123



	Blue
170-145	Excel Cat6A Solid Patch Lead U/FTP Shielded LS0H Cca Blade Booted 10m Ice Blue
170-146	Excel Category 6A Solid Patch Lead U/FTP Shielded LS0H Cca Blade Booted 20m - Ice Blue
170-147	Excel Cat6A Solid Patch Lead U/FTP Shielded LS0H Cca Blade Booted 30m Ice Blue

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.