

Item Code: 180-205



✕ VL UL94

✕ EN 45545

✕ NF F16-101 / F16-102

✕ Halogen free

Product Overview

Excel sleeving is designed in such a way as to allow the diameter to expand either by compressing the sleeving or by the insertion of cable and/or components. It is perfect for looming a number of different data cables together.

Supplied in an easy pull style box, plastic packaging free.

Flame Resistance: Self Extinguishing (V2 UL94)

Product Specifications

Feature	Values
Bundle diameter	10...20 mm
Material	PET
Halogen free	yes
Colour	Black
Temperature	-50...130 °C
Fire resistance in accordance with UL94	V2
Approved according to NF F 16-101	yes

Standards

Applicable standard	Detail
RoHS-II/-III (2011/65/EU & 2015/863): 2023	Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).
WFD: 2023	Compliant to Waste Framework Directive
SCIP: 2023	Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
POPs (EU) No 2019/1021	EU Regulation for the restriction of Persistent Organic Pollutants.

Part Number Table

Part Number	Description
180-202	Cable Binding Polyethylene Wrap 6mm - 22mm 25m
180-205	Braided Sleeving Expandable 10mm - 20mm 100m
180-208	Braided Sleeving Expandable 40mm - 63mm 25m

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com