## Item Code: 190-910-1000M





### **Product Overview**

Excel Category 7A screened S/FTP cable is designed and manufactured to meet and exceed the ISO, CENELEC and TIA standards. This delivers Class FA link and channel performance supporting all applications detailed and proposed within the standards. This superior performance cable is ETL Component Verified.


Each cable consists of 4 pairs individually wrapped in a covering of high quality, strong, aluminium/polyester foil tape providing an individual screen for each pair. These sub units are then cabled together, with the pairs set to different lay lengths to ensure optimum performance, an overall braid screen is applied to provide further immunity to outside noise and to mitigate any risk of alien cross talk.

The print legend on the cable now includes information regarding the DOP number, Test and Classification of the cable for traceability.

### **Product Specifications**

| Feature                       | Values            |
|-------------------------------|-------------------|
| Conductor surface             | Bare              |
| AWG size                      | 23                |
| Conductor category            | Class $1 = solid$ |
| Total number of cores         | 8                 |
| Stranding element             | Pairs             |
| Specification core insulation | Polyethylene (PE) |
| Core identification           | Colour            |
| Overall screening             | Braiding          |

# Excel Solid Cat7A Cable S/FTP B2ca LS0H 1000 m Reel Yellow





| Conductor screening   | Foil                            |
|---|---------------------------------|
| Outer sheath material   | Copolymer, thermoplastic (LS0H) |
| Outer sheath colour   | Yellow                          |
| Flame retardant according to IEC 60332-1-2                    | yes                             |
| Reaction-to-fire class according to EN 13501-6                | B2ca                            |
| Smoke development class according to EN 13501-6               | sla                             |
| Euro class flaming droplets/particles according to EN 13501-6 | d1                              |
| Euro class acidity according to EN 13501-6                    | al                              |
| Outer diameter approx.  | 7.8 mm                          |
| Installation Temperature Range                                | 060 °C                          |
| Operating Temperature Range                                   | -2060 °C                        |
| Category  | 7A (IEC)                        |
| NVP value   | 76 %                            |

#### **Part Number Table**

| Part Number   | Description   |
|---------------|---|
| 100-910       | Excel Solid Cat7A Cable S/FTP Dca LS0H 500 m Reel Yellow          |
| 100-910-1000  | Excel Solid Cat7A Cable S/FTP Dca LS0H 1000 m Reel Yellow         |
| 100-910-GRY   | Excel Category 7A Cable S/FTP Dca LS0H 500m Reel - Grey           |
| 100-910-VT    | Excel Category 7A Cable S/FTP Dca LS0H 500m Reel - Violet         |
| 100-911       | Excel Dual Cat7A Cable S/FTP Dca LS0H 500 m Reel Yellow           |
| 100-912       | Excel Category 7A+ Cable S/FTP Dca LS0H 500 m Reel - Yellow       |
| 190-910       | Excel Solid Cat7A Cable S/FTP B2ca LS0H 500 m Reel Yellow         |
| 190-910-1000M | Excel Solid Cat7A Cable S/FTP B2ca LS0H 1000 m Reel Yellow        |
| 190-910-VT    | Excel Solid Cat7A Cable S/FTP B2ca LS0H 500 m Reel Violet         |
| 190-912       | Excel Solid Cat7A+ Cable S/FTP 22 AWG B2ca LS0H 500 m Reel Yellow |

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.