

Excel Solid Cat7A Cable S/FTP LSOH B2ca 1000 m Reel Yellow

excel
without compromise.

Part Code: 190-910-1000M

sales@excel-networking.com
excel-networking.com

CIBSE TM65 Embodied Carbon: 451.105 kg CO2e



Main Features

- / Individual foil pairs with overall braid screen
- / Category 7A performance to 1000 MHz
- / Sequential metre markings
- / Euroclass B2ca-s1a-d1-a1
- / CIBSE TM65 Embodied Carbon: 451.105 kg CO2e

Product Overview

Excel Category 7A screened S/FTP cable is designed and manufactured to meet and exceed the ISO, CENELEC and TIA standards. This delivers Class FA link and channel performance supporting all applications detailed and proposed within the standards. This superior performance cable is ETL Component Verified.

Each cable consists of 4 pairs individually wrapped in a covering of high quality, strong, aluminium/polyester foil tape providing an individual screen for each pair. These sub units are then cabled together, with the pairs set to different lay lengths to ensure optimum performance, an overall braid screen is applied to provide further immunity to outside noise and to mitigate any risk of alien cross talk.

The print legend on the cable now includes information regarding the DOP number, Test and Classification of the cable for traceability.

Excel Solid Cat7A Cable S/FTP LSOH B2ca 1000 m Reel Yellow

Part Code: 190-910-1000M

sales@excel-networking.com
excel-networking.com

Product Specifications

Feature	Values
Cable type	S/FTP
Conductor material	Copper
Conductor surface	Bare
AWG size	23
Conductor category	Class 1 = solid
Total number of cores	8
Stranding element	Pairs
Specification core insulation	Polyethylene (PE)
Core identification	Colour
Overall screening	Braiding
Conductor screening	Foil
Outer sheath material	Copolymer, thermoplastic (LSOH)
Outer sheath colour	Yellow
Flame retardant according to IEC 60332-1-2	yes
Reaction-to-fire class according to EN 13501-6	B2ca
Smoke development class according to EN 13501-6	s1a
Euro class flaming droplets/particles according to EN 13501-6	d1
Euro class acidity according to EN 13501-6	a1
Outer diameter approx.	7.8 mm
Installation Temperature Range	0...60 °C
Operating Temperature Range	-20...60 °C
Category	7A (IEC)

Excel Solid Cat7A Cable S/FTP LSOH B2ca 1000 m Reel Yellow



Part Code: 190-910-1000M

sales@excel-networking.com
excel-networking.com

NVP value

76%

Part Code Table

Part Code	Description
190-910-1000M	Excel Solid Cat7A S/FTP B2ca LSOH 1000 m RI Yellow