

Excel Cat6A Zone Cable U/FTP 26AWG LSOH CPR
Euroclass B2ca 305 m Box Ice Blue

Item Code: 190-982



- ✕ Cat6A 26AWG solid copper cable
- ✕ Suitable for installations to 60 m PL, 70 m CL
- ✕ U/FTP no overall screening
- ✕ Foil screen per pair
- ✕ Outer sheath colour: Ice blue
- ✕ Reaction-to-fire class according to EN 13501-6: B2ca

Product Overview

Excel Cat6A zone cable U/FTP 26AWG LSOH is manufactured to meet and exceed the ISO, CENELEC and TIA standards up to 60 m permanent link or 70 m channel link. It is not a full blown Cat6A cable and is only intended for data centre zone or residential use where distances beyond 60 m are not required.

Excel Cat6A screened (U/FTP) cable takes the performance capabilities of copper infrastructure to new levels. This delivers Class EA/Augmented Category 6 link performance over distances of up to 70 m channel which supports the applications including 10GBASE-T, 10 Gigabit Ethernet and PoE++.

Each cable consists of 4 pairs of 26AWG solid cores individually wrapped in high quality, strong, aluminium/polyester foil tape providing screening for each pair.

The foil configuration ensures separation of the pairs that ensures the performance and the individual pairs are set to different lay lengths to ensure optimum performance.

Product Specifications

Feature	Values
Conductor surface	Bare
AWG size	26
Conductor category	Class 1 = solid
Total number of cores	8


Excel Cat6A Zone Cable U/FTP 26AWG LSOH CPR
Euroclass B2ca 305 m Box Ice Blue

Item Code: 190-982



Stranding element	Pairs
Specification core insulation	Polyethylene (PE)
Core identification	Colour
Overall screening	None
Conductor screening	Foil
Outer sheath material	Copolymer, thermoplastic (LSOH)
Outer sheath colour	Ice blue
Flame retardant according to IEC 60332-1-2	yes
Low smoke (acc. IEC 61034-2)	yes
Reaction-to-fire class according to EN 13501-6	B2ca
Smoke development class according to EN 13501-6	s1a
Euro class flaming droplets/particles according to EN 13501-6	d1
Euro class acidity according to EN 13501-6	a1
Outer diameter approx.	5.88 mm
Operating Temperature Range	-10...60 °C
Category	6A (IEC)
NVP value	69.5 %

Product drawing



Additional specifications

Features	Values
Dielectric strength	1.7 kV for 2 s
Maximum pulling load	50 N
MBR during installation	8x cable OD
MBR installed	4x cable OD

Standards

Applicable standard	Detail
ISO/IEC 11801:2017	Information technology - Generic cabling for customer premises: Part 1 General requirements
IEC 61156-5:2020	Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1000 MHz - Horizontal floor wiring - Sectional specification
EN 50173-1:2018	Information technology - Generic cabling systems -

Excel Cat6A Zone Cable U/FTP 26AWG LSOH CPR Euroclass B2ca 305 m Box Ice Blue

Item Code: 190-982



General requirements

EN 50173-2:2018	Information technology - Generic cabling systems - Office premises
BS EN 50288-3-1:2013	Multi-element metallic cables used in analogue and digital communication and control. Sectional specification for unscreened cables characterised up to 250 MHz
EN 50399:2011+A1:2016	Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results
IEC 60332-1-2:2004 + A12:2020	Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame
ANSI/TIA 568-D:2015	Balanced Twisted-Pair Telecommunications Cabling and Components Standards
IEC 60754-2:2014	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity
IEC 61034-2:2005+A2:2020	Measurement of smoke density of cables burning under defined conditions - Part 2: Test procedure and requirements
EN 50575:2014 + A1:2016	Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements
IEEE 802.3bt (Type 4)	Compliant to IEEE 802.3bt (Type 4)
RoHS-II/-III (2011/65/EU & 2015/863): 2023	Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).
WFD: 2023	Compliant to Waste Framework Directive
SCIP: 2023	Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
POPs (EU) No 2019/1021	EU Regulation for the restriction of Persistent Organic Pollutants.

Part Number Table

Part Number	Description
100-982	Excel Cat6A Zone Cable U/FTP 26AWG LSOH CPR Euroclass Dca 305 m Box White

Excel Cat6A Zone Cable U/FTP 26AWG LSOH CPR
Euroclass B2ca 305 m Box Ice Blue
Item Code: 190-982



190-982	Excel Cat6A Zone Cable U/FTP 26AWG LSOH CPR Euroclass B2ca 305 m Box Ice Blue
---------	---

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.