### Excel Cat6A Solid Core U/FTP 26AWG Screened Harness Link Leads B2ca 10 m Aqua

Item Code: 190-982-10-MF









- X Category 6A compliant
- X Solid core cable
- For switch/harness links and CP cables
- X LSOH outer sheath
- X Euroclass: B2ca-s1a,d1,a1

#### **Product Overview**

Excel Category 6A solid core (F/FTP) Zone screened harness/switch link leads are constructed from 190-982 Excel solid 26AWG Cat6A cable F/FTP LSOH screened cable ice blue (horizontal cable). Each of these leads allows the construction of two switch/harness links or Consolidation Point (CP) cables.

The lead is manufactured with a high performance screened RJ45 plug on each end permitting the lead to be cut into two at the required lengths. Slimline blade strain relief boots are fitted to protect the latch and allow connection to the highest density equipment.

Using the same cable as the horizontal elements of the channel assures performance and does not "use up" the stranded patch lead allowance. These leads are for the creation of switch/harness links and CP cables.

They are not for use as a replacement for patch leads.

#### **Product Specifications**

Feature	Values
Cable type	F/FTP
Category	6A (IEC)
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
Outer sheath colour	Aqua
Strain relief boot	Push-on
Lockable	no
Strain relief boot colour	Black
Flame retardant version	yes

# Excel Cat6A Solid Core U/FTP 26AWG Screened Harness Link Leads B2ca 10 m Aqua

Item Code: 190-982-10-MF



Halogen free (acc. IEC 60754-2)	yes
Cable construction	1x4
AWG-size	26
Pin assignment	1:1

### **Standards**

Detail
Information technology - Generic cabling for customer premises: Part 1 General Requirements
Information technology. Generic cabling systems - General requirements
Balanced Twisted-Pair Telecommunications Cabling and Components Standards
Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Horizontal floor wiring - Sectional specification
Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame
Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements
Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results
Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements
Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).
Compliant to Waste Framework Directive
Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
EU Regulation for the restriction of Persistent Organic

# Excel Cat6A Solid Core U/FTP 26AWG Screened Harness Link Leads B2ca 10 m Aqua

Item Code: 190-982-10-MF



### **Part Number Table**

Part Number	Description
190-982-10-MF	Excel Cat6A Solid Core U/FTP 26AWG Screened Harness Link Leads B2ca 10 m Aqua
190-982-15-MF	Excel Cat6A Solid Core U/FTP 26AWG Screened Harness Link Leads B2ca 15 m Aqua
190-982-20-MF	Excel Cat6A Solid Core U/FTP 26AWG Screened Harness Link Leads B2ca 20 m Aqua
190-982-25-MF	Excel Cat6A Solid Core U/FTP 26AWG Screened Harness Link Leads B2ca 25 m Aqua
190-982-30-MF	Excel Cat6A Solid Core U/FTP 26AWG Screened Harness Link Leads B2ca 30 m Aqua

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.