


# Excel Enbeam OM2 Fibre Optic Patch Lead LC-ST Multimode 50/125 DX LS0H Orange 10 m

Part Code: 200-180

sales@excel-networking.com  
excel-networking.com



## Main Features

- / 100% Optically Tested
- / Low Loss Connectors
- / Polarity Changeable (Duplex Connectors)
- / Test Certificate Included
- / Zirconia ceramic UPC ferrules
- / Bend insensitive construction

## Product Overview

Excel OM2 50/125µm duplex patch leads are manufactured from the highest quality 900 µm buffer/jacket optical fibre, terminated with ceramic ferrule connectors.

Each cable has strain relief boots to prolong and maintain performance levels of the assembly, transmit and receive 'legs' of each duplex cable are identified by means of ring type cable marker fixed to each end the assembly. A short distance from these identification rings heat shrink is applied to maintain an easy to manage bonded two fibre cable, finally a label containing a unique batch number is fixed to the centre of cable for quality and traceability purposes.

# Excel Enbeam OM2 Fibre Optic Patch Lead LC-ST Multimode 50/125 DX LS0H Orange 10 m

Part Code: 200-180

sales@excel-networking.com  
excel-networking.com

## Product Specifications

| Feature                                    | Values            |
|--|-------------------|
| Fibre type                                 | Multi mode 50/125 |
| Category                                   | OM2               |
| Number of Cores                            | 2                 |
| Outer diameter sheath single fibre         | 2 mm              |
| Cable type                                 | Duplex            |
| Length                                     | 10 m              |
| Type of connector connection 1             | LC                |
| Type of connector connection 2             | ST                |
| Outer sheath colour                        | Orange            |
| Strain relief boot                         | Push-on           |
| Flame retardant according to IEC 60332-1-2 | yes               |
| Low smoke (acc. IEC 61034-2)               | yes               |

## Cable specifications

| Features           | Values          | ST Assemblies | SC Assemblies | LC Assemblies |
|--------------------|-----------------|---------------|---------------|---------------|
| Cable Construction | Duplex zip-cord |               |               |               |
| No. of Fibres      | 2               |               |               |               |
| Cable Dimensions   |                 | 2.8 x 5.7mm   | 2.8 x 5.7mm   | 2.0 x 4.0mm   |
| Colour             | Orange          |               |               |               |
| Strength members   | Aramid Yarn     |               |               |               |

# Excel Enbeam OM2 Fibre Optic Patch Lead LC-ST Multimode 50/125 DX LS0H Orange 10 m

Part Code: 200-180

sales@excel-networking.com  
excel-networking.com

|                              |                                |                                |                                 |
|------------------------------|--------------------------------|--------------------------------|---------------------------------|
| Temperature range            | <b>-20C to +70C</b>            |                                |                                 |
| Connector Material           | <b>Nickel plated Brass</b>     | <b>Composite</b>               | <b>Composite</b>                |
| Minimum bend radius (loaded) | <b>10 x cable diameter</b>     |                                |                                 |
| Connector Ferrule            | <b>2.5mm Zirconium ceramic</b> | <b>2.5mm Zirconium ceramic</b> | <b>1.25mm Zirconium ceramic</b> |
| Ferrule End Face             | <b>PC Polish</b>               |                                |                                 |
| Connector Insertion Loss     | <b>Max. 0.3dB</b>              |                                |                                 |

## Fibre specifications

| Features                             | Values                |
|--------------------------------------|-----------------------|
| Core diameter                        | <b>50 ± 2.5µm</b>     |
| Core Non-circularity                 | <b>≤5%</b>            |
| Core-Cladding Concentricity Error    | <b>≤1.5µm</b>         |
| Cladding diameter                    | <b>125 ± 1.0µm</b>    |
| Cladding Non-circularity             | <b>≤1.0%</b>          |
| Primary Coating diameter             | <b>245 ± 7µm</b>      |
| Coating-Cladding Concentricity Error | <b>≤10.0µm</b>        |
| Coating Non-circularity              | <b>≤6.0%</b>          |
| Secondary coating diameter           | <b>900 µm nominal</b> |
| Max. attenuation at 850nm            | <b>2.3dB/km</b>       |
| Max attenuation at 1300nm            | <b>0.6dB/km</b>       |

# Excel Enbeam OM2 Fibre Optic Patch Lead LC-ST Multimode 50/125 DX LS0H Orange 10 m

Part Code: 200-180

sales@excel-networking.com  
excel-networking.com

|   |                     |
|---|---------------------|
| Refractive Index at 850nm                         | <b>1.482</b>        |
| Refractive Index at 1300nm                        | <b>1.477</b>        |
| Bandwidth at 850nm                                | <b>500 MHz.km</b>   |
| Bandwidth at 1300nm                               | <b>500 MHz.km</b>   |
| Numerical Aperture                                | <b>0.200 ±0.015</b> |
| Zero Dispersion Wavelength                        | <b>1295-1340nm</b>  |
| Macrobending Loss - 2 turns, 15mm Radius, 850nm   | <b>≤0.10dB</b>      |
| Macrobending Loss - 2 turns, 15mm Radius, 1300nm  | <b>≤0.30dB</b>      |
| Macrobending Loss - 2 turns, 7.5mm Radius, 850nm  | <b>≤0.2dB</b>       |
| Macrobending Loss - 2 turns, 7.5mm Radius, 1300nm | <b>≤0.5dB</b>       |
| Coating Strip Force (typical)                     | <b>1.5N</b>         |
| Coating Strip Force (peak)                        | <b>1.3 - 8.9N</b>   |

# Excel Enbeam OM2 Fibre Optic Patch Lead LC-ST Multimode 50/125 DX LSOH Orange 10 m

Part Code: 200-180

sales@excel-networking.com  
excel-networking.com

## Cross-section diagram



## Product Schematics



- 1 ST Dust cover
- 2 ST 3.0 multimode connector\*
- 3 ST 3.0 Black strain relief boot\*
- 4 ST 3.0 Red strain relief boot\*
- 5 Identification ring
- 6 Black heatshrink tubing
- 7 3.0mm Duplex OM1 62.5/125 LSOH Grey or Orange cable\*

\* 2.0 when used in hybrid cables with LC or MTRJ connectors

- 1 SC Dust cover
- 2 SC 3.0 Beige multimode connector\*
- 3 SC Beige clip
- 4 SC 3.0 Black strain relief boot\*
- 5 SC 3.0 Red strain relief boot\*
- 6 Identification ring
- 7 Black heatshrink tubing
- 8 3.0mm Duplex OM1 62.5/125 LSOH Grey or Orange cable\*

\* 2.0 when used in hybrid cables with LC or MTRJ connectors

- 1 LC Dust cover
- 2 LC 2.0 multimode simplex Beige connector
- 3 LC Beige clip
- 4 LC 2.0 white boot
- 5 White heatshrink tubing
- 6 Yellow heatshrink tubing
- 7 Identification ring
- 8 Black heatshrink tubing
- 9 2.0mm Duplex OM1 62.5/125 LSOH Grey or Orange cable

# Excel Enbeam OM2 Fibre Optic Patch Lead LC-ST Multimode 50/125 DX LS0H Orange 10 m

Part Code: 200-180

sales@excel-networking.com  
excel-networking.com

## Standards

| Applicable standard           | Detail  |
|-------------------------------|---|
| BS EN 60332-1-2:2004+A11:2016 | Tests on electric and optical fibre cables under fire conditions - Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame |
| IEC 60793-1-1:2022            | Optical fibres - Part 1-1: Measurement methods and test procedures - General and guidance   |
| IEC 60793-2:2015              | Optical fibres - Part 2: Product specifications - General   |
| IEC 60793-2-10:2017           | Sectional specification for A1 multimode fibres   |
| IEC 60793-1-20:2014           | Optical fibres - Part 1-20: Measurement methods and test procedures - Fibre geometry  |
| IEC 60793-1-21:2001           | Optical fibres - Part 1-21: Measurement methods and test procedures - Coating geometry  |
| IEC 60793-1-22:2001           | Optical fibres - Part 1-22: Measurement methods and test procedures - Length measurement  |
| IEC 60793-1-30:2010           | Optical fibres - Part 1-30: Measurement methods and test procedures - Fibre proof test  |
| IEC 60793-1-31:2010           | Optical fibres - Part 1-31: Measurement methods and test procedures - Tensile Strength  |
| ITU G.651.1                   | Characteristics of a 50/125 $\mu\text{m}$ multimode graded index optical fibre cable for the optical access network   |
| EN 50173-1:2018               | Information technology. Generic cabling systems - General requirements  |
| EN 50173-2:2007 + A1:2010     | Information technology. Generic cabling systems - Office premises   |
| IEC 61754-1:2013              | Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 1: General and guidance  |
| IEC 61754-2:1996              | Fibre optic connector interfaces - Part 2: Type BFOC/2,5 connector family   |

# Excel Enbeam OM2 Fibre Optic Patch Lead LC-ST Multimode 50/125 DX LS0H Orange 10 m

Part Code: 200-180

sales@excel-networking.com  
excel-networking.com

|                                    |  |
|------------------------------------|--|
| IEC 61754-4:2013                   | Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 4: Type SC connector family   |
| IEC 61754-4-100:2015               | Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 4-100: Type SC connector family - Simplified receptacle SC-PC connector interfaces  |
| IEC 61754-20:2012                  | Fibre optic connector interfaces - Part 20: Type LC connector family   |
| Directive 2011/65/EU (RoHS II)     | Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).   |
| Directive (EU) 2015/863 (RoHS III) | Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.   |
| Directive 2008/98/EC (WFD)         | Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).   |
| ECHA SCIP Database                 | Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.  |
| Regulation (EU) 2019/1021 (POPs)   | EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).   |
| UKSI 2012 No. 3032                 | The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019. |

# Excel Enbeam OM2 Fibre Optic Patch Lead LC-ST Multimode 50/125 DX LS0H Orange 10 m

Part Code: 200-180

sales@excel-networking.com  
excel-networking.com

## Part Code Table

| Part Code | Description  |
|-----------|--|
| 200-093   | Excel Enbeam OM2 Fibre Optic Patch Lead LC-SC Multimode 50/125 DX LS0H Orange 10 m |
| 200-094   | Excel Enbeam OM2 Fibre Optic Patch Lead LC-SC Multimode 50/125 DX LS0H Orange 15 m |
| 200-095   | Excel Enbeam OM2 Fibre Optic Patch Lead LC-SC Multimode 50/125 DX LS0H Orange 20 m |
| 200-168   | Excel Enbeam OM2 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LS0H Orange 1 m  |
| 200-169   | Excel Enbeam OM2 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LS0H Orange 2 m  |
| 200-170   | Excel Enbeam OM2 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LS0H Orange 3 m  |
| 200-171   | Excel Enbeam OM2 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LS0H Orange 5 m  |
| 200-172   | Excel Enbeam OM2 Fibre Optic Patch Lead LC-SC Multimode 50/125 DX LS0H Orange 1 m  |
| 200-173   | Excel Enbeam OM2 Fibre Optic Patch Lead LC-SC Multimode 50/125 DX LS0H Orange 2 m  |
| 200-174   | Excel Enbeam OM2 Fibre Optic Patch Lead LC-SC Multimode 50/125 DX LS0H Orange 3 m  |
| 200-175   | Excel Enbeam OM2 Fibre Optic Patch Lead LC-SC Multimode 50/125 DX LS0H Orange 5 m  |
| 200-176   | Excel Enbeam OM2 Fibre Optic Patch Lead LC-ST Multimode 50/125 DX LS0H Orange 1 m  |
| 200-177   | Excel Enbeam OM2 Fibre Optic Patch Lead LC-ST Multimode 50/125 DX LS0H Orange 2 m  |
| 200-178   | Excel Enbeam OM2 Fibre Optic Patch Lead LC-ST Multimode 50/125 DX LS0H Orange 3 m  |

# Excel Enbeam OM2 Fibre Optic Patch Lead LC-ST Multimode 50/125 DX LS0H Orange 10 m

Part Code: 200-180

sales@excel-networking.com  
excel-networking.com

|         |  |
|---------|--|
| 200-179 | Excel Enbeam OM2 Fibre Optic Patch Lead LC-ST Multimode 50/125 DX LS0H Orange 5 m  |
| 200-180 | Excel Enbeam OM2 Fibre Optic Patch Lead LC-ST Multimode 50/125 DX LS0H Orange 10 m |
| 200-200 | Excel Enbeam OM2 Fibre Optic Patch Lead ST-ST Multimode 50/125 DX LS0H Orange 1 m  |
| 200-202 | Excel Enbeam OM2 Fibre Optic Patch Lead ST-ST Multimode 50/125 DX LS0H Orange 2 m  |
| 200-204 | Excel Enbeam OM2 Fibre Optic Patch Lead ST-ST Multimode 50/125 DX LS0H Orange 3 m  |
| 200-206 | Excel Enbeam OM2 Fibre Optic Patch Lead ST-ST Multimode 50/125 DX LS0H Orange 5 m  |
| 200-209 | Excel Enbeam OM2 Fibre Optic Patch Lead ST-ST Multimode 50/125 DX LS0H Orange 10 m |
| 200-216 | Excel Enbeam OM2 Fibre Optic Patch Lead ST-SC Multimode 50/125 DX LS0H Orange 1 m  |
| 200-218 | Excel Enbeam OM2 Fibre Optic Patch Lead ST-SC Multimode 50/125 DX LS0H Orange 2 m  |
| 200-219 | Excel Enbeam OM2 Fibre Optic Patch Lead ST-SC Multimode 50/125 DX LS0H Orange 15 m |
| 200-220 | Excel Enbeam OM2 Fibre Optic Patch Lead ST-SC Multimode 50/125 DX LS0H Orange 3 m  |
| 200-222 | Excel Enbeam OM2 Fibre Optic Patch Lead ST-SC Multimode 50/125 DX LS0H Orange 5 m  |
| 200-224 | Excel Enbeam OM2 Fibre Optic Patch Lead SC-SC Multimode 50/125 DX LS0H Orange 1 m  |
| 200-226 | Excel Enbeam OM2 Fibre Optic Patch Lead SC-SC Multimode 50/125 DX LS0H Orange 2 m  |
| 200-227 | Excel Enbeam OM2 Fibre Optic Patch Lead ST-SC Multimode 50/125 DX LS0H Orange 10 m |
| 200-228 | Excel Enbeam OM2 Fibre Optic Patch Lead SC-SC Multimode 50/125 DX LS0H Orange 3 m  |
| 200-229 | Excel Enbeam OM2 Fibre Optic Patch Lead SC-SC Multimode 50/125 DX LS0H             |

# Excel Enbeam OM2 Fibre Optic Patch Lead LC-ST Multimode 50/125 DX LS0H Orange 10 m

Part Code: 200-180

sales@excel-networking.com  
excel-networking.com

## Orange 5 m

|         |   |
|---------|---|
| 200-236 | Excel Enbeam OM2 Fibre Optic Patch Lead SC-SC Multimode 50/125 DX LS0H Orange 10 m  |
| 200-237 | Excel Enbeam OM2 Fibre Optic Patch Lead SC-SC Multimode 50/125 DX LS0H Orange 15 m  |
| 200-238 | Excel Enbeam OM2 Fibre Optic Patch Lead SC-SC Multimode 50/125 DX LS0H Orange 20 m  |
| 200-265 | Excel Enbeam OM2 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LS0H Orange 10 m  |
| 200-266 | Excel Enbeam OM2 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LS0H Orange 15 m  |
| 200-267 | Excel Enbeam OM2 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LS0H Orange 20 m  |
| 200-286 | Excel Enbeam OM2 Fibre Optic Patch Lead ST-ST Multimode 50/125 DX LS0H Orange 15 m  |
| 200-287 | Excel Enbeam OM2 Fibre Optic Patch Lead ST-ST Multimode 50/125 DX LS0H Orange 20 m  |
| 200-533 | Excel Enbeam OM2 Fibre Optic Patch Lead LC-ST Multimode 50/125 DX LS0H Orange 20 m  |
| 202-171 | Excel Enbeam OM2 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LS0H Orange 0.5 m |
| 202-174 | Excel Enbeam OM2 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LS0H Orange 30 m  |
| 202-178 | Excel Enbeam OM2 Fibre Optic Patch Lead LC-SC Multimode 50/125 DX LS0H Orange 0.5 m |
| 202-181 | Excel Enbeam OM2 Fibre Optic Patch Lead LC-SC Multimode 50/125 DX LS0H Orange 30 m  |
| 202-184 | Excel Enbeam OM2 Fibre Optic Patch Lead LC-ST Multimode 50/125 DX LS0H Orange 0.5 m |
| 202-191 | Excel Enbeam OM2 Fibre Optic Patch Lead SC-SC Multimode 50/125 DX LS0H Orange 0.5 m |
| 202-194 | Excel Enbeam OM2 Fibre Optic Patch Lead SC-SC Multimode 50/125 DX LS0H Orange 30 m  |

Excel Enbeam OM2 Fibre Optic Patch Lead LC-ST  
Multimode 50/125 DX LS0H Orange 10 m



Part Code: 200-180

sales@excel-networking.com  
excel-networking.com

202-197

Excel Enbeam OM2 Fibre Optic Patch Lead ST-ST Multimode 50/125 DX LS0H  
Orange 0.5 m