



✗ 25 year system warranty

✗ Available in Single mode & Multi mode

✗ Dust caps included

Product Overview

Excel Enbeam fibre optic adaptors have been designed to present a range of optic fibre connectors. The adaptors are constructed to allow fitting in the bulkheads with nuts. The housings are manufactured from a range of metals selected to provide the optimum performance.

Product Specifications

Feature	Values
Suitable for type of fibre	Single mode
Type of connector connection 1	FC
Type of connector connection 2	FC
Material housing	Metal
Type of fastening	Screw
Colour	Silver
APC-type	no

Additional specifications

Features	Values
Insertion Loss	< 0.2 dB
Durability (500 Mating)	0.2 dB Max Increase
Operating Temperature	-40°C to +80°C
Retention Force	200 - 600 grams

Standards

Applicable standard	Detail
IEC 61300-2-22	Fibre optic interconnecting devices and passive components - Basic test and measurement procedures Change of temperature
IEC 61300-3-4:2012	Fibre optic interconnecting devices and passive components - Basic test and measurement procedures Attenuation
IEC 61300-2-2	Fibre optic interconnecting devices and passive components - Basic test and measurement procedures Mating durability

Part Number Table

Part Number	Description
200-389-06	Excel Enbeam FC Simplex Multimode Adaptor (6-Pack)
200-390	Excel Enbeam FC Simplex Singlemode Adaptor

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.

