Excel Enbeam FTTx Outlet up to 4 Fibres (Unloaded)

Part Code: 200-446

sales@excel-networking.com
excel-networking.com



Main Features

- Hinged splice tray holds up to 4 heatshrink splice protectors
- Fixing hardware included
- Accepts LC duplex or SC simplex adaptors
- Multiple cable entry points
- For use with flangeless adaptors
- 2x 40 mm splice protectors supplied as standard

Product Overview

The Excel Enbeam FTTx Surface Mount Box has been designed for applications such as Fibre to the home or Fibre to the Desk.

Product Specifications

Feature	Values
Surface mounted	**yes**

This data sheet was generated at 5:57pm 15th November 2026 and is subject to change at any time.

With couplers	**no**
Suitable for number of couplers	**2**
Suitable for type of fibre	**Multi mode/single mode**
Width	**82.5 mm**
Height	**105 mm**
Depth	**25.5 mm**

Additional specifications

Features	Values
Capacity for 2 port	**4 Fibres**
Capacity for 4 port	**8 Fibres**
Material	**ABS Plastic**
Colour	**White**
Weight	**83 grams**
Operating Temprature	**-20 to +85 °C**


Included accessories

Accessories	2-port	4-port
Splice Protectors	**2**	**4**
Wall fixings	**1 set**	**1 set**

This data sheet was generated at 5:57pm 15th November 2026 and is subject to change at any time.

sales@excel-networking.com
excel-networking.com

Product drawing



Standards

Applicable standard	Detail
IEC 61754-1:2013	Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 1: General and guidance
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
UL-94-V-0	Burning stops within 10 seconds after two applications of ten seconds each of a flame to a test bar. NO flaming drips are allowed.
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article

This data sheet was generated at 5:57pm 15th November 2026 and is subject to change at any time.

	33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
UK SI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

Part Code Table

Part Code	Description
200-446	**Excel Enbeam FTTx Outlet up to 4 Fibres (Unloaded)**
200-447	**Excel Enbeam FTTx Outlet Loaded with 2x SC/APC OS1/OS2 Simplex Adaptors**
200-448	**Excel Enbeam FTTx Outlet up to 8 Fibres (Unloaded)**
200-449	**Excel Enbeam FTTx Outlet Loaded with 4x SC/APC Simplex Adaptors**
200-449-ITS	**Excel Enbeam FTTx Outlet Loaded with 4x SC/APC Simplex Adaptors**

This data sheet was generated at 5:57pm 15th November 2026 and is subject to change at any time.