

Excel Enbeam FTTx Outlet up to 4 Fibres (Unloaded)

Item Code: 200-446



✕ Hinged splice tray holds up to 4 heatshrink splice protectors

✕ Multiple cable entry points

✕ Fixing hardware included

✕ For use with flangeless adaptors

✕ Accepts LC duplex or SC simplex adaptors

✕ 2x 40 mm splice protectors supplied as standard

Product Overview

The Excel Enbeam FTTx Surface Mount Box has been designed for applications such as Fibre to the home or Fibre to the Desk.

Product Specifications

Feature	Values
Surface mounted	yes
With couplers	no
Suitable for number of couplers	2
Suitable for type of fibre	Multi mode/single mode
Width	82.5 mm
Height	105 mm
Depth	25.5 mm

Item Code: 200-446


Additional specifications

Features	Values
Capacity for 2 port	4 Fibres
Capacity for 4 port	8 Fibres
Material	ABS Plastic
Colour	White
Weight	83 grams
Operating Temperature	-20 to +85 °C

Included accessories

Accessories	2-port	4-port
Splice Protectors	2	4
Wall fixings	1 set	1 set

Product drawing



Standards

Applicable standard	Detail
IEC 61754-1:2013	Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 1: General and guidance
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements

Excel Enbeam FTTx Outlet up to 4 Fibres (Unloaded)



Item Code: 200-446

EN 50173-1:2018

Information technology. Generic cabling systems - General requirements

UL-94-V-0

Burning stops within 10 seconds after two applications of ten seconds each of a flame to a test bar. NO flaming drips are allowed.

RoHS-II/-III (2011/65/EU & 2015/863): 2023

Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).

WFD: 2023

Compliant to Waste Framework Directive

SCIP: 2023

Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)

POPs (EU) No 2019/1021

EU Regulation for the restriction of Persistent Organic Pollutants.

Part Number Table

Part Number	Description
200-446	Excel Enbeam FTTx Outlet up to 4 Fibres (Unloaded)
200-447	Excel Enbeam FTTx Outlet Loaded with 2x SC/APC OS1/OS2 Simplex Adaptors
200-448	Excel Enbeam FTTx Outlet up to 8 Fibres (Unloaded)
200-449	Excel Enbeam FTTx Outlet Loaded with 4x SC/APC Simplex Adaptors

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.