Item Code: 200-449-70





	Hinged Splice Tray holds up to 8 heatshrink splice
	protectors

- X Multiple cable entry points
- X Fixing hardware included
- X Loaded with 4 X SCA Shuttered adapters
- X Pre terminated with 4 core Cca drop cable

#### **Product Overview**

The Excel Enbeam FTTx Surface mount box has been designed for applications such as Fibre to the Home or Fibre to the Desk. This Wall outlet can also be fitted with a DIN rail mounting plate for installations requiring Din mounting capability. Pre terminate with a 4 core 250 Micron Cca,s1a,d0,a1 drop cable 70 m in length terminated one end with 4 x SC APC connectors and open at the other, allows quick installation within the customer premises.

#### **Product Specifications**

Feature	Values
Surface mounted	yes
Type of connector	SC/APC simplex
With couplers	yes
Suitable for number of couplers	4
Suitable for type of fibre	Single mode
Width	100 mm
Height	80.6 mm
Depth	29.5 mm

Item Code: 200-449-70




### **Additional specifications**

Features	Values
Capacity	4 Fibre
Material	ABS Plastic
Colour	White
Operating Temprature	-20 to +85 °C
Drop Cable	
Cable Diameter	3mm
Fibre type	9/125 G657-A2
Number of cores	4
Core size	250um
Colour	RAL 9010
Operating temprature	-20°C ~ +70°C
Reaction-to-fire class according to EN 13501-6	B2ca
Smoke development class according to EN 13501-6	sla
Euro class flaming droplets/particles according to EN 13501-6	d0
Euro class acidity according to EN 13501-6	al

Item Code: 200-449-70



### **Cross-section view (drop cable)**



#### **Standards**

Applicable standard	Detail
RoHS-II/-III (2011/65/EU & 2015/863): 2023	Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).
IEC 61754-1:2013	Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 1: General and guidance
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
UL-94-V-0	Burning stops within 10 seconds after two applications of ten seconds each of a fl ame to a test bar. NO fl aming drips are allowed.
WFD: 2023	Compliant to Waste Framework Directive
SCIP: 2023	Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
POPs (EU) No 2019/1021	EU Regulation for the restriction of Persistent Organic Pollutants.

Item Code: 200-449-70



#### **Part Number Table**

Part Number	Description
200-449-30	Excel Enbeam FTTx 4 Port SC Outlet with 30 m Drop Cable
200-449-50	Excel Enbeam FTTx 4 Port SC Outlet with 50 m Drop Cable
200-449-70	Excel Enbeam FTTx 4 Port SC Outlet with 70 m Drop Cable

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.