


# Excel Enbeam Fibre Pigtail OS2 9/125 LC/APC Yellow 1m (12-Pack)

excel  
without compromise.

Part Code: 200-655

sales@excel-networking.com  
excel-networking.com

CIBSE TM65 Embodied Carbon: 0.133 kg CO2e



## Main Features

- / G.657.A2 Compliant
- / Choice of lengths
- / Easy strip
- / Pack of 12
- / Test Certificate with each cable
- / RoHS Compliant

## Product Overview

Excel singlemode fibre optic pigtails are manufactured from the highest quality 900 micron optical fibre, terminated with ceramic ferrule connectors of various types. To assist in fast cable preparation and splicing semi tight buffered, easy strip, cable is used as standard. Cable preparation, termination and testing is carried out to strictly managed procedures in an Excel approved, ISO9001 registered manufacturing facility.

Each pigtail has a strain relief boot to prolong and maintain performance levels of the assembly. A short distance from the connector a label containing a unique batch number is fixed to cable for quality and traceability purposes.

# Excel Enbeam Fibre Pigtail OS2 9/125 LC/APC Yellow 1 m (12-Pack)

Part Code: 200-655

sales@excel-networking.com  
excel-networking.com

## Product Specifications

Feature	Values
Fibre type	Single mode
Category	OS2
Length	1 m
Type of connector	LC
APC-type	yes
Colour	Yellow
Strain relief boot	Push-on

Excel Enbeam Fibre Pigtail OS2 9/125 LC/APC Yellow 1m  
(12-Pack)



Part Code: 200-655

sales@excel-networking.com  
excel-networking.com

## Product schematics

# Excel Enbeam Fibre Pigtail OS2 9/125 LC/APC Yellow 1m (12-Pack)

Part Code: 200-655

sales@excel-networking.com  
excel-networking.com

ST



- ① ST Dust cover
- ② ST connector
- ③ ST Strain relief boot
- ④ Easy Strip LSOH cable

SC



- ① SC Dust cover
- ② SC connector
- ③ SC Strain relief boot
- ④ Easy Strip LSOH cable

LC




- ① LC Dust cover
- ② LC connector
- ③ LC Strain relief boot
- ④ Easy Strip LSOH cable

FC




- ① FC Dust cover
- ② FC connector
- ③ FC Strain relief boot
- ④ Easy Strip LSOH cable

## Cable Profile



## Packaging



# Excel Enbeam Fibre Pigtail OS2 9/125 LC/APC Yellow 1m (12-Pack)

Part Code: 200-655

sales@excel-networking.com  
excel-networking.com

## Fibre specifications

Features	Values
Mode Field diameter at 1310 nm	8.4-9.2 $\mu\text{m}$
Mode Field diameter at 1550 nm	9.3-10.3 $\mu\text{m}$
Cladding diameter	125.0 $\pm$ 0.7 $\mu\text{m}$
Cladding Non-circularity	$\leq$ 0.7 %
Primary Coating diameter	235-245 $\mu\text{m}$
Coating-Cladding Concentricity Error	$\leq$ 12 $\mu\text{m}$
Coating Non-circularity	$\leq$ 6.0 %
Core-Cladding Concentricity Error	$\leq$ 0.5 $\mu\text{m}$
Max. attenuation at 1310 nm	$\leq$ 0.35 dB/km
Max. attenuation at 1383 nm	$\leq$ 0.35 dB/km
Max. attenuation at 1460 nm	$\leq$ 0.25 dB/km
Max. attenuation at 1490 nm	$\leq$ 0.23 dB/km
Max attenuation at 1550 nm	$\leq$ 0.21 dB/km
Max attenuation at 1625 nm	$\leq$ 0.23 dB/km
PMD (typical value)	0.04 ps/km
Cut-off wavelength	1260 nm
Zero dispersion wavelength	1300-1324 nm
Zero dispersion slope	$\leq$ 0.092 ps/nm <sup>2</sup> .km
Refractive Index at 1310 nm	1.466
Refractive Index at 1550 nm	1.467
Macro-Bend Loss - 10 turns, 15 mm radius, 1625 nm	$\leq$ 0.0 3dB

# Excel Enbeam Fibre Pigtail OS2 9/125 LC/APC Yellow 1m (12-Pack)

Part Code: 200-655

sales@excel-networking.com  
excel-networking.com

Macro-Bend Loss - 10 turns, 15 mm radius, 1550 nm	≤ 0.1 dB
Macro-Bend Loss - 1 turn, 10 mm radius, 1550 nm	≤ 0.1 dB
Macro-Bend Loss - 1 turn, 10 mm radius, 1625 nm	≤ 0.2 dB
Macro-Bend Loss - 1 turn, 7.5 mm radius, 1550 nm	≤ 0.5 dB
Macro-Bend Loss - 1 turn, 7.5 mm radius, 1625 nm	≤ 1.0 dB

## Cable specifications

Features	Values	ST Assemblies	SC Assemblies	LC Assemblies
Construction	<b>Semi-Tight Buffered</b>			
No. of Fibres	<b>1</b>			
Diameter	<b>900 micron</b>			
Temperature range	<b>-20C to +70C</b>			
Connector Material		<b>Nickel plated Brass</b>	<b>Composite</b>	<b>Composite</b>
Minimum bend radius	<b>10 x cable diameter</b>			
Connector Ferrule		<b>2.5 mm Zirconium ceramic</b>	<b>2.5 mm Zirconium ceramic</b>	<b>1.25 mm Zirconium ceramic</b>
Connector Insertion Loss	<b>Max. 0.3 dB</b>			
Connector Return Loss (Multimode)	<b>Max. -30 dB</b>			
Ferrule End Face (Singlemode UPC)	<b>Max. -50 dB</b>			

# Excel Enbeam Fibre Pigtail OS2 9/125 LC/APC Yellow 1 m (12-Pack)

Part Code: 200-655

sales@excel-networking.com  
excel-networking.com

Ferrule End Face  
(Singlemode APC) **Max. -60 dB**

## Standards

Applicable standard	Detail
IEC 60793-1-1:2022	Optical fibres - Part 1-1: Measurement methods and test procedures - General and guidance
IEC 60793-2:2015	Optical fibres - Part 2: Product specifications - General
IEC 60793-2-10:2017	Sectional specification for A1 multimode fibres
IEC 60793-1-20:2014	Optical fibres - Part 1-20: Measurement methods and test procedures - Fibre geometry
IEC 60793-1-21:2001	Optical fibres - Part 1-21: Measurement methods and test procedures - Coating geometry
IEC 60793-1-22:2001	Optical fibres - Part 1-22: Measurement methods and test procedures - Length measurement
IEC 60793-1-30:2010	Optical fibres - Part 1-30: Measurement methods and test procedures - Fibre proof test
IEC 60793-1-31:2010	Optical fibres - Part 1-31: Measurement methods and test procedures - Tensile Strength
ITU-T G652.1:2016	Characteristics of a 9/125 $\mu\text{m}$ multimode graded index optical fibre cable for the optical access network
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
EN 50173-2:2007 + A1:2010	Information technology. Generic cabling systems - Office premises
IEC 61754-1:2013	Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 1: General and guidance
IEC 61754-2:1996	Fibre optic connector interfaces - Part 2: Type BFOC/2,5

# Excel Enbeam Fibre Pigtail OS2 9/125 LC/APC Yellow 1m (12-Pack)

Part Code: 200-655

sales@excel-networking.com  
excel-networking.com

## connector family

IEC 61754-4:2013	Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 4: Type SC connector family
IEC 61754-4-100:2015	Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 4-100: Type SC connector family - Simplified receptacle SC-PC connector interfaces
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
ANSI/TIA 568-3.D	Optical Fiber Cabling and Components Standard
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
UKSI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

# Excel Enbeam Fibre Pigtail OS2 9/125 LC/APC Yellow 1 m (12-Pack)

Part Code: 200-655

sales@excel-networking.com  
excel-networking.com

## Part Code Table

Part Code	Description
200-648	Excel Enbeam Fibre Pigtail OS2 9/125 ST/UPC Yellow 1 m (12-Pack)
200-649	Excel Enbeam Fibre Pigtail OS2 9/125 SC/UPC Yellow 1 m (12-Pack)
200-650	Excel Enbeam Fibre Pigtail OS2 9/125 LC/UPC Yellow 1 m (12-Pack)
200-653	Excel Enbeam Fibre Pigtail OS2 9/125 SC/APC Clear White 1 m (12-Pack)
200-654	Excel Enbeam Fibre Pigtail OS2 9/125 FC/UPC Clear White 1 m (12-Pack)
200-655	Excel Enbeam Fibre Pigtail OS2 9/125 LC/APC Yellow 1m (12-Pack)