

Excel Enbeam 12 Way SC Fibre + 12 Port Unloaded RJ45 Hybrid Panel

Part Code: 200-940

sales@excel-networking.com
excel-networking.com



Main Features

- / Accepts 12 fibre and 12 copper connections
- / Port identification numbers
- / Multiple cable entry to rear
- / Management and fixing kit included

Product Overview

The Excel Hybrid patch panel are sliding drawer tray style housings suitable for either direct termination or splicing of upto 12 fibres and 12 RJ45 Keystone jacks in 1U of rack space.

Each panel is manufactured from high quality 1.2mm thick steel powder coat finish to provide a strong and durable unit. To the front of the patch panel the specified number of adaptors are loaded from left to right.

Each panel utilises colour coded adaptors and the ability to install 12 RJ45 keystone jack to the requirements of each installation.

Each panel has included within it a set of fixing brackets, and a cable management pack which includes cable entry glands, cable ties, and a 24 way splice bridge.

Excel Enbeam 12 Way SC Fibre + 12 Port Unloaded RJ45 Hybrid Panel

Part Code: 200-940

sales@excel-networking.com
excel-networking.com

Product Specifications


Feature	Values
Suitable for number of fibre cores	12
Suitable for number of module inserts	12
With pigtails	no
Fibre type	Single mode
Fibre class	OS2
APC-type	yes
Type of connector external	SC-Simplex
Type of connector interior	SC-Simplex
Colour	Black
RAL-number	9005
Mounting method	482.6 mm (19 inch) mounting
Number of rack units (RU)	1
Height	43.5 mm
Width	483 mm
Depth	219.5 mm

Excel Enbeam 12 Way SC Fibre + 12 Port Unloaded RJ45 Hybrid Panel

Part Code: 200-940

sales@excel-networking.com
excel-networking.com

Product drawing



Additional specifications

Features	Values
Operating temperature	-40 to +80 °C
IP rating	IP20
Cable entry 20mm	1

Excel Enbeam 12 Way SC Fibre + 12 Port Unloaded RJ45 Hybrid Panel

Part Code: 200-940

sales@excel-networking.com
excel-networking.com

Cable entry 25mm	1
Material	Cold rolled steel
Material thickness	1.2mm
Material coating	Powder coating
RoHS compliant	Yes
Designed in accordance with	ISO/IEC 11801; IEC60304; IEC61754; TIA/EIA 568.D

Included accessories

Accessories	Quantity
Cable gland (PG13.5)	1
Cable gland (PG19)	1
Nylon cable ties	7
24 position splice holder	1
Mounting twist ties	4
Cage nuts and screws	1pk

Standards

Applicable standard	Detail
IEC 61754-1:2013	Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 1: General and guidance
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements

Excel Enbeam 12 Way SC Fibre + 12 Port Unloaded RJ45 Hybrid Panel

Part Code: 200-940

sales@excel-networking.com
excel-networking.com

EN 50173-1:2011	Information technology. Generic cabling systems - General requirements
UL-94-V-0	Burning stops within 10 seconds after two applications of ten seconds each of a flame to a test bar. No flaming drips are allowed.
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
UK SI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

Part Code Table

Part Code	Description
200-940	Excel Enbeam 12 Way SC Fibre + 12 Port Unloaded RJ45 Hybrid Panel
200-941	Excel Enbeam 12 Way SC/APC Fibre + 12 Port Unloaded RJ45 Hybrid Panel