
Excel Enbeam OS2 Fibre Optic Patch Lead G.657 LC-LC Singlemode 9/125 DX LS0H Blue 5 m

Part Code: 200-966

sales@excel-networking.com
excel-networking.com



Main Features

- G657 Bend insensitive fibre
- 2.0 mm cable
- Blue outer sheath
- 25 Year system warranty

Product Overview

The Enbeam range of patch cords are constructed from high quality connectors and G657 bend intensive 9/125 µm OS2 grade cable. Each cable has a short strain relief boot and is supplied with atest report detailing insertion loss. All the patch cords come with a blue outer sheath and are individually packaged and labelled.

Product Specifications

Feature	Values

This data sheet was generated at 2:16am 17th November 2026 and is subject to change at any time.


Excel Enbeam OS2 Fibre Optic Patch Lead G.657 LC-LC Singlemode 9/125 DX LS0H Blue 5 m

Part Code: 200-966

sales@excel-networking.com
excel-networking.com


Fibre type	**Single mode**
Category	**OS2**
Number of Cores	**2**
Outer diameter sheath single fibre	**2 mm**
Cable type	**Duplex**
Length	**5 m**
Type of connector connection 1	**LC**
Type of connector connection 2	**LC**
Outer sheath colour	**Blue**
Strain relief boot	**Push-on**
Flame retardant according to IEC 60332-1-2	**yes**
Low smoke (acc. IEC 61034-2)	**yes**

Cross-section diagram



This data sheet was generated at 2:16am 17th November 2026 and is subject to change at any time.

Product drawing



Standards

Applicable standard	Detail
BS EN 60332-1-2:2004+A11:2016	Tests on electric and optical fibre cables under fire conditions - Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame
IEC 60793-1-1:2022	Optical fibres - Part 1-1: Measurement methods and test procedures - General and guidance
IEC 60793-2:2015	Optical fibres - Part 2: Product specifications - General
IEC 60793-2-10:2017	Sectional specification for A1 multimode fibres
IEC 60793-1-20:2014	Optical fibres - Part 1-20: Measurement methods and test procedures - Fibre geometry
IEC 60793-1-21:2001	Optical fibres - Part 1-21: Measurement methods and test procedures - Coating geometry

This data sheet was generated at 2:16am 17th November 2026 and is subject to change at any time.

IEC 60793-1-22:2001	Optical fibres - Part 1-22: Measurement methods and test procedures - Length measurement
IEC 60793-1-30:2010	Optical fibres - Part 1-30: Measurement methods and test procedures - Fibre proof test
IEC 60793-1-31:2010	Optical fibres - Part 1-31: Measurement methods and test procedures - Tensile Strength
ITU-T G.652:2016	Characteristics of a single-mode optical fibre and cable
ITU-T G.657:2016	Characteristics of a bending-loss insensitive single-mode optical fibre and cable
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
EN 50173-2:2007 + A1:2010	Information technology. Generic cabling systems - Office premises
IEC 61754-1:2013	Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 1: General and guidance
IEC 61754-2:1996	Fibre optic connector interfaces - Part 2: Type BFOC/2,5 connector family
IEC 61754-4:2013	Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 4: Type SC connector family
IEC 61754-4-100:2015	Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 4-100: Type SC connector family - Simplified receptacle SC-PC connector interfaces
IEC 61754-20:2012	Fibre optic connector interfaces - Part 20: Type LC connector family
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.

This data sheet was generated at 2:16am 17th November 2026 and is subject to change at any time.

Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
UK SI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

Part Code Table

Part Code	Description
200-953	**Excel Enbeam OS2 Fibre Optic Patch Lead G.657 SC-SC Singlemode 9/125 DX LS0H Blue 1 m**
200-954	**Excel Enbeam OS2 Fibre Optic Patch Lead G.657 SC-SC Singlemode 9/125 DX LS0H Blue 2 m**
200-955	**Excel Enbeam OS2 Fibre Optic Patch Lead G.657 SC-SC Singlemode 9/125 DX LS0H Blue 3 m**
200-956	**Excel Enbeam OS2 Fibre Optic Patch Lead G.657 SC-SC Singlemode 9/125 DX LS0H Blue 5 m**
200-957	**Excel Enbeam OS2 Fibre Optic Patch Lead G.657 SC-SC Singlemode 9/125 DX LS0H Blue 10 m**
200-958	**Excel Enbeam OS2 Fibre Optic Patch Lead G.657 LC-SC Singlemode 9/125 DX LS0H Blue 1 m**
200-959	**Excel Enbeam OS2 Fibre Optic Patch Lead G.657 LC-SC Singlemode 9/125 DX**

This data sheet was generated at 2:16am 17th November 2026 and is subject to change at any time.

	LS0H Blue 2 m
200-960	**Excel Enbeam OS2 Fibre Optic Patch Lead G.657 LC-SC Singlemode 9/125 DX LS0H Blue 3 m**
200-961	**Excel Enbeam OS2 Fibre Optic Patch Lead G.657 LC-SC Singlemode 9/125 DX LS0H Blue 5 m**
200-962	**Excel Enbeam OS2 Fibre Optic Patch Lead G.657 LC-SC Singlemode 9/125 DX LS0H Blue 10 m**
200-963	**Excel Enbeam OS2 Fibre Optic Patch Lead G.657 LC-LC Singlemode 9/125 DX LS0H Blue 1 m**
200-964	**Excel Enbeam OS2 Fibre Optic Patch Lead G.657 LC-LC Singlemode 9/125 DX LS0H Blue 2 m**
200-965	**Excel Enbeam OS2 Fibre Optic Patch Lead G.657 LC-LC Singlemode 9/125 DX LS0H Blue 3 m**
200-966	**Excel Enbeam OS2 Fibre Optic Patch Lead G.657 LC-LC Singlemode 9/125 DX LS0H Blue 5 m**
200-967	**Excel Enbeam OS2 Fibre Optic Patch Lead G.657 LC-LC Singlemode 9/125 DX LS0H Blue 10 m**

This data sheet was generated at 2:16am 17th November 2026 and is subject to change at any time.