Item Code: 201-627









X Multimode/singlemode options available
X Choice of port density
X Management and fixing kit included
X Adjustable fixing arms included
X Multiple cable entry to rear
X Sliding drawer on ball bearing runners

Product Overview

The Excel range of LC patch panels are sliding drawer "tray style" housings suitable for either direct termination or splicing of up to 48 fibres in 1U of rack space. Each panel is manufactured from high quality 2 mm thick steel and finished in Black powder coat to provide a strong and durable unit.

Up to 48 fibres

To the front of the patch panel the specified number of adaptors are loaded from left to right. Each panel utilises colour coded adaptors, beige, aqua and violet for multimode, blue for singlemode, and green for SM APC. Each duplex (or quad) adaptor accommodates two (four) terminated fibres.

Each panel has included within it a set of fixing brackets, and a cable management pack which includes cable entry glands, cable ties, splice holders, cage nuts and screws are also provided.

Note that LC panels can be assembled to order using a combination of adaptors, pigtails and splice cassettes.

Product Specifications

Feature	Values
Suitable for number of fibre cores	48
Suitable for number of module inserts	24
Loaded with number of couplings/adapters	24
With pigtails	no
Fibre type	Multi mode 50/125

Item Code: 201-627



Fibre class	OM4/OM3/OM2
APC-type	no
Type of connector external	LC-Duplex
Type of connector interior	LC-Duplex
Colour	Black
RAL-number	9005
Mounting method	482.6 mm (19 inch) mounting
Number of rack units (RU)	1
Height	43.5 mm
Width	483 mm
Depth	219.5 mm

Additional specifications

Feature	Value
Operating Temprature	-40 to +80 °C
IP Rating	IP20
Cable Entry 20mm	2
Cable Entry 25mm	2
Material	Cold rolled steel
Material Thickness	2mm
Material Coating	Powder Coating
RoHs Compliant Adaptor	Yes
Designed in accordance with	ISO/IEC 11801, IEC60304,IEC61754, TIA/EIA 568.D

Included accessories

Accessories	Quantity
Cable Gland (PG 13.5)	1
Cable Gland(PG 19)	1
Nylon cable tie	7
Adjustable cable tie	4
24 Position splice Cassette	2

Item Code: 201-627



Label holder (210 x 9.2 mm)	2
Mounting twist tie	4
Cage nuts and screws	1pk


Item Code: 201-627



Product drawing

Item Code: 201-627





Item Code: 201-627



Standards

Applicable standard	Detail
RoHS-II/-III (2011/65/EU & 2015/863): 2023	Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).
WFD: 2023	Compliant to Waste Framework Directive
SCIP: 2023	Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
POPs (EU) No 2019/1021	EU Regulation for the restriction of Persistent Organic Pollutants.

Part Number Table

Part Number	Description
201-620	Excel Enbeam 24 Way SM OS2 Fibre Optic Panel 24 LC Duplex 48F + Pigtail & Cassette
201-621	Excel Enbeam 24 Way SM OS2 Fibre Optic Panel 4 LC/APC Duplex 48F + Pigtail & Cassette
201-622	Excel Enbeam 24 Way MM OM3 Fibre Optic Panel 24 LC Duplex 48F + Pigtail $\&$ Cassette
201-623	Excel Enbeam 24 Way MM OM4 Fibre Optic Panel 24 LC Duplex 48F + Pigtail & Cassette
201-624	Excel Enbeam 24 Way SM OS2 Fibre Optic Panel 24 LC Duplex 48F + Cassette
201-625	Excel Enbeam 24 Way SM OS2 Fibre Optic Panel 24 LC/APC Duplex 48F + Cassette
201-626	Excel Enbeam 24 Way MM OM3 Fibre Optic Panel 24 LC Duplex 48F + Cassette
201-627	Excel Enbeam 24 Way MM OM4 Fibre Optic Panel 24 LC Duplex 48F + Cassette

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.