



- ✗ Cut-outs to suit any glanding configuration can be drilled on site
- ✗ Comes with 4 entry points
- ✗ Comes with 2 PG 9 and 2 PG 21 glands
- ✗ 25 Year system warranty
- ✗ CIBSE TM65 Embodied Carbon: 38.167 kg CO2e

Product Overview

These patch boxes and splice enclosures are manufactured from impact resistant steel and provide a cost effective means of breaking out fibres from multicore cables prior to termination or splicing. The boxes provide protection against water and dust ingress to IP65. The lids are attached using captive screws.

Product Specifications

Feature	Values
Mounting method	Surface mounted
Type of covering	Door
Type of door	Single
Transparent cover/door	no
Height	430 mm
Width	330 mm
Depth	199 mm
Colour	White
Material housing	Steel
IP-rating	IP65

Standards

Applicable standard	Detail
RoHS-II-III (2011/65/EU & 2015/863): 2023	Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).
WFD: 2023	Compliant to Waste Framework Directive
SCIP: 2023	Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
POPs (EU) No 2019/1021	EU Regulation for the restriction of Persistent Organic Pollutants.

Part Number Table

Part Number	Description
202-040	Excel Enbeam 12 Fibre Junction Splice Box Splice Kit
202-041	Excel Enbeam 24 Fibre Junction Splice Box Lockable Splice Kit
202-120	Excel Enbeam 24 Fibre Steel Splice Box Unloaded

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.

