

# Excel Enbeam 24 Way Multimode Fibre Optic Panel 24 LC Quad (96 Fibre) Aqua

excel  
without compromise.

Part Code: 203-553-PL

sales@excel-networking.com  
excel-networking.com



## Main Features

- / New plastic tray design
- / High density up to 96 fibres
- / Port identification numbers
- / Multiple cable entry to rear
- / 1U rack space design
- / 25 year system warranty

## Product Overview

The Excel range of LC patch panels are sliding drawer "tray style" housings suitable for either direct termination or splicing of up to 96 fibres in 1U of rack space. Each Panel is manufactured from black UL94-V0 ABS plastic and a metal support frame providing a strong and durable unit. To the front of the patch panel the specified number of adaptors are loaded from left to right. Each panel utilises colour coded adaptors, beige, aqua and violet for multimode, blue for singlemode, and green for Singlemode APC. Each duplex (or quad) adaptor accommodates two (four) terminated fibres. Each panel has included within it a set of fixing brackets, and a cable management pack which includes cable entry glands, cable ties, splice holders, cage nuts and screws are also provided. Note: Removal tool 208-172 is required to remove adaptors. Reduction in emissions Reduced mineral extraction Reduction in embedded carbon by...

# Excel Enbeam 24 Way Multimode Fibre Optic Panel 24 LC Quad (96 Fibre) Aqua

Part Code: 203-553-PL

sales@excel-networking.com  
excel-networking.com

## Product Specifications

Feature	Values
Suitable for number of fibre cores	96
Suitable for number of module inserts	24
Loaded with number of couplings/adapters	24
With pigtails	no
Fibre type	Multi mode 50/125
Fibre class	OM3
APC-type	no
Type of connector external	LC-Quad
Type of connector interior	LC-Quad
Colour	Black
RAL-number	9005
Mounting method	482.6 mm (19 inch) mounting
Number of rack units (RU)	1
Height	43.8 mm
Width	482 mm
Depth	216.3 mm

## Additional specifications

Feature	Value
Operating Temperature	-40 to +80 °C
IP Rating	IP20

# Excel Enbeam 24 Way Multimode Fibre Optic Panel 24 LC Quad (96 Fibre) Aqua

Part Code: 203-553-PL

sales@excel-networking.com  
excel-networking.com

Cable Entry 20 mm	2
Cable Entry 25 mm	2
Material	<b>ABS and cold rolled steel</b>
Material Thickness	<b>1.2 mm</b>
Material Coating	<b>Powder coating</b>
RoHs Compliant Adaptor	<b>Yes</b>
Designed in accordance with	<b>ISO/IEC 11801, IEC60304, IEC61754, TIA/EIA 568.D</b>

## Included accessories

Accessories	Quantity
Cable Gland (PG 13.5)	1
Cable Gland (PG 19)	1
Nylon cable tie	7
Adjustable cable tie	4
24 Position splice holder	<b>1 to 3 Dependant on fibre count</b>
Label holder (210 x 9.2 mm)	2
Mounting twist tie	4
Cage nuts and screws	<b>1 pack</b>

Excel Enbeam 24 Way Multimode Fibre Optic Panel 24 LC  
Quad (96 Fibre) Aqua



Part Code: 203-553-PL

sales@excel-networking.com  
excel-networking.com



Product drawing



# Excel Enbeam 24 Way Multimode Fibre Optic Panel 24 LC Quad (96 Fibre) Aqua

Part Code: 203-553-PL

sales@excel-networking.com  
excel-networking.com



LC quadruplex adaptor with dust caps

# Excel Enbeam 24 Way Multimode Fibre Optic Panel 24 LC Quad (96 Fibre) Aqua

Part Code: 203-553-PL

sales@excel-networking.com  
excel-networking.com

## Standards

Applicable standard	Detail
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
UK SI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

## Part Code Table

Part Code	Description
200-488-PL	<b>Excel Enbeam 24 Way Singlemode Fibre Optic Panel 24 LC Quad (96 Fibre) Blue</b>
200-489-PL	<b>Excel Enbeam 24 Way Multimode Fibre Optic Panel 24 LC Quad (96 Fibre) Beige</b>
203-553-PL	<b>Excel Enbeam 24 Way Multimode Fibre Optic Panel 24 LC Quad (96 Fibre) Aqua</b>

Excel Enbeam 24 Way Multimode Fibre Optic Panel 24 LC  
Quad (96 Fibre) Aqua



Part Code: 203-553-PL

sales@excel-networking.com  
excel-networking.com

204-553-PL

Excel Enbeam 24 Way Multimode Fibre Optic Panel 24 LC Quad (96 Fibre)  
Violet