



✗ Duct grade rodent resistant

✗ Cut to length service

✗ Sequentially metre marked

✗ 25 Year system warranty

✗ Euroclass Dca-s2-d2-a1

✗ CIBSE TM65 Embodied Carbon: 0.190 kg CO2e

Product Overview

Excel OM4 50/125 μm loose tube optical fibre cables have been designed specifically for internal and external applications. These compact, lightweight cables are extremely flexible and are quick and easy to install.

The cables are constructed around a gel filled (non-dripping and silicon free) tube containing up to 24 colour coded 250 μm primary coated fibres. This tube is covered with an E-Glass strength member.


The print legend on the cable now includes information regarding the DOP number, Test and Classification of the cable for traceability.

Product Specifications


Feature	Values
Number of Cores	6
Type of tube	Loose tube
Number of fibres per tube	6
Fibre type	Multi mode 50/125
Category	OM4
Rodent resistant	yes
Outer sheath material	Copolymer, thermoplastic (LSOH)
Outer sheath colour	Black
Flame retardant according to IEC 60332-1-2	yes

Low smoke (acc. IEC 61034-2)	yes
Reaction-to-fire class according to EN 13501-6	Dca
Smoke development class according to EN 13501-6	s2
Euro class flaming droplets/particles according to EN 13501-6	d2
Euro class acidity according to EN 13501-6	a1
Outer diameter approx.	6 mm

Cross-section diagram



Colour coding (as per TIA-598-C)



For fibre core counts above 12 the colour sequence is repeated with the addition of a mark every 70mm for cores 13-24 and two marks for 25-36 and so on.

Cable specifications

Features	Values
Loose Tube	Material
	PBT
	Diameter
	$2.8 \pm 0.1\text{mm}$ (2-12 cores), $3.5 \pm 0.20\text{mm}$ (16-24 cores)
	Thickness
	$0.35 \pm 0.05\text{mm}$

Excel Enbeam OM4 Multimode Fibre Optic Cable Loose Tube 6 Core 50/125 Dca Black

Item Code: 204-006



Strength Member	Material	E-glass Yarns
Sheath	Material	LSZH
	Thickness	Typical 1.1mm
Cable Diameter	Diameter ($\pm 0.3\text{mm}$)	$6.0 \pm 0.20\text{mm}$ (2-16 cores), $6.5 \pm 0.20\text{mm}$ (18-24 cores)
Cable Weight		Approx. 40kg/km(2-16 cores), 45kg/km(18-24 cores)
Tensile Strength	Installation	1000N
	Working	300N
Cable Impact		1J
Crush Resistance	Installation	1000N
	Working	300N
Torsion		Change of Attenuation $\leq 0.10\text{dB}$ (SM fiber)
		Change of Attenuation $\leq 0.30\text{dB}$ (MM fiber)
Temperature Range	Installation	-30°C to +60°C
	Working	-30°C to +60°C
	Storage	-40°C to +60°C
Bending Radius	Short term	20 x Diameter
	Long term	10 x Diameter
Water Penetration		No water on free end

Fibre specifications

Features	Values
Attenuation	@850 nm 3.5dB/km (maximum)
	@1300 nm 1.5dB/km (maximum)
	For any 1000 metre Max. 0.1dB/km
Overfilled modal bandwidth	@850 nm $\geq 3500\text{ MHz/km}$
	@1300 nm $\geq 500\text{ MHz/km}$
Effective modal bandwidth	@850 nm $\geq 4700\text{ MHz/km}$
Core diameter	$50 \pm 2.5\text{ }\mu\text{m}$
Core non-circularity	$\leq 5\%$

Cladding diameter	125.0±1.0 μ m	
Cladding non-circularity	\leq 1%	
Core - cladding concentricity error	\leq 1.5 μ m	
Primary coating diameter - uncolored	242±7 μ m	
Primary coating diameter - colored	250±15 μ m	
Primary coating non-circularity	\leq 5%	
Primary coating - cladding concentricity error	\leq 12 μ m	
Group index of refraction	@850 nm	1.482
	@1300 nm	1.477
Proof stress level	\geq 0.7(\approx 1% strain) Gpa	
Typical average strip force	1.7 N	
Strip force (peak)	1.3 \leq Fpeak.strip \leq 8.9 N	
Numerical aperture	0.200 \pm 0.015	
Fiber bending loss R-7.5 mm	@850 nm	\leq 0.2dB
	@1300 nm	\leq 0.5dB
Fiber bending loss R-15 mm	@850 nm	\leq 0.1dB
	@1300 nm	\leq 0.3dB

Standards

Applicable standard	Subject
IEC 60794-2-20:2013	Optical fibre cables - Part 2-20: Indoor cables - Family specification for multi-fibre optical cables
IEC 60332-1-2:2004	Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame
IEC 60754-2:2011	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity
IEC 61034-2:2005+A1:2013	Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements
IEC 60793-1-1:2022	Optical fibres - Part 1-1: Measurement methods and test procedures - General and guidance

Excel Enbeam OM4 Multimode Fibre Optic Cable Loose Tube 6 Core 50/125 Dca Black

Item Code: 204-006



IEC 60793-2-10:2017	Sectional specification for A1 multimode fibres
IEC 60793-1-20:2014	Optical fibres - Part 1-20: Measurement methods and test procedures - Fibre geometry
IEC 60793-1-21:2001	Optical fibres - Part 1-21: Measurement methods and test procedures - Coating geometry
IEC 60793-1-22:2001	Optical fibres - Part 1-22: Measurement methods and test procedures - Length measurement
IEC 60793-1-30:2010	Optical fibres - Part 1-30: Measurement methods and test procedures - Fibre proof test
IEC 60793-1-41:2010	Optical fibres - Part 1-41: Measurement methods and test procedures - Bandwidth
ITU G.651.1	Characteristics of a 50/125 μm multimode graded index optical fibre cable for the optical access network
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
EN 50575: 2014 + A1: 2016	Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements
EN 50399:2011+A1:2016	Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
ANSI/TIA 568-3.D	Optical Fiber Cabling and Components Standard
ANSI/TIA/EIA 598-D	Optical Fibre Cable Colour Coding
RoHS-II/-III (2011/65/EU & 2015/863): 2023	Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).
WFD: 2023	Compliant to Waste Framework Directive
SCIP: 2023	Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
POPs (EU) No 2019/1021	EU Regulation for the restriction of Persistent Organic Pollutants.

Part Number Table

Part Number	Description
204-004	Excel Enbeam OM4 Multimode Fibre Optic Cable Loose Tube 4 Core 50/125 LSOH Dca Black
204-006	Excel Enbeam OM4 Multimode Fibre Optic Cable Loose Tube 6 Core 50/125 Dca Black
204-008	Excel Enbeam OM4 Multimode Fibre Optic Cable Loose Tube 8 Core 50/125 LSOH Dca Black
204-012	Excel Enbeam OM4 Multimode Fibre Optic Cable Loose Tube 12 Core 50/125 LSOH Dca Black
204-016	Excel Enbeam OM4 Multimode Fibre Optic Cable Loose Tube 16 Core 50/125 LSOH Dca Black
204-024	Excel Enbeam OM4 Multimode Fibre Optic Cable Loose Tube 24 Core 50/125 LSOH Dca Black

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.

excel
without compromise.