
# Excel Enbeam OM4 Fibre Optic Patch Lead SC-SC Multimode 50/125 DX LS0H Violet 3 m

**Part Code: 204-340**

sales@excel-networking.com
excel-networking.com



## Main Features

- / 100% optically tested
- / Low loss connectors
- / Polarity changeable (duplex connectors)
- / Test certificate included
- / Zirconia ceramic UPC ferrules
- / Bend insensitive construction

## Product Overview

Excel OM4 50/125 µm duplex patch leads are manufactured from the highest quality 900 µm buffer/jacket optical fibre, terminated with ceramic ferrule connectors.

Each cable has strain relief boots to prolong and maintain performance levels of the assembly, transmit and receive "legs" of each duplex cable are identified by means of ring type cable marker fixed to each end the assembly. A short distance from these identification rings heat shrink is applied to maintain an easy to manage bonded two fibre cable, finally a label containing a unique batch number is fixed to the centre of cable for quality and traceability purposes.


This data sheet was generated at 4:37am 7th November 2026 and is subject to change at any time.

# Excel Enbeam OM4 Fibre Optic Patch Lead SC-SC Multimode 50/125 DX LS0H Violet 3 m

**Part Code: 204-340**

sales@excel-networking.com
excel-networking.com

## Product Specifications

| Feature | Values |
|---|---|
| Fibre type | **Multi mode 50/125** |
| Category | **OM4** |
| Number of Cores | **2** |
| Outer diameter sheath single fibre | **3 mm** |
| Cable type | **Duplex** |
| Length | **3 m** |
| Type of connector connection 1 | **SC** |
| Type of connector connection 2 | **SC** |
| Outer sheath colour | **Violet** |
| Strain relief boot | **Push-on** |
| Flame retardant according to IEC 60332-1-2 | **yes** |
| Low smoke (acc. IEC 61034-2) | **yes** |

## Cable specifications

| Features | Values | SC Assemblies | LC Assemblies |
|---|---|---|---|
| Cable Construction | **Duplex zip-cord** | | |
| No. of Fibres | **2** | | |
| Cable Dimensions | | **2.8 x 5.7mm** | **2.0 x 4.0mm** |
| Colour | **Heather Violet** | | |
| Strength members | **Aramid Yarn** | | |
| Temperature range | **-20C to +70C** | | |


This data sheet was generated at 4:37am 7th November 2026 and is subject to change at any time.

| | | | |
|---|---|---|---|
| Connector Material | | **Composite** | **Composite** |
| Minimum bend radius (loaded) | **10 x cable diameter** | | |
| Connector Ferrule | | **2.5mm Zirconium ceramic** | **1.25mm Zirconium ceramic** |
| Ferrule End Face | **PC Polish** | | |
| Connector Insertion Loss | **Max. 0.3dB** | | |


## Fibre specifications

| Features | Values |
|---|---|
| Core diameter | **50 ± 2.5μm** |
| Core Non-circularity | **≤5%** |
| Core-Cladding Concentricity Error | **≤1.0μm** |
| Cladding diameter | **125 ± 1.0μm** |
| Cladding Non-circularity | **≤1.0%** |
| Primary Coating diameter | **245 ± 7μm** |
| Coating-Cladding Concentricity Error | **≤10.0μm** |
| Coating Non-circularity | **≤6.0%** |
| Secondary coating diameter | **900 μm nominal** |
| Max. attenuation at 850nm | **2.4dB/km** |
| Max attenuation at 1300nm | **0.6dB/km** |
| Refractive Index at 850nm | **1.482** |
| Refractive Index at 1300nm | **1.477** |
| >=Bandwidth at 850nm | **≥3500 MHz.km** |


This data sheet was generated at 4:37am 7th November 2026 and is subject to change at any time.

| | |
|---|---|
| Bandwidth at 1300nm | **≥500 MHz.km** |
| Effective Modal Bandwidth at 850nm | **≥4700 MHz/km** |
| Numerical Aperture | **0.200 ±0.015** |
| Zero Dispersion Wavelength | **1295-1340nm** |
| Macrobending Loss - 100 turns, 37.5mm Radius, 850nm | **≤0.50dB** |
| Macrobending Loss - 100 turns, 37.5mm Radius, 1300nm | **≤0.50dB** |
| Macrobending Loss - 2 turns, 15mm Radius, 850nm | **≤1.0dB** |
| Macrobending Loss - 2 turns, 15mm Radius, 1300nm | **≤1.0dB** |
| Coating Strip Force (typical) | **1.5N** |
| Coating Strip Force (peak) | **1.3 - 8.9N** |

## Cross-section diagram






This data sheet was generated at 4:37am 7th November 2026 and is subject to change at any time.

sales@excel-networking.com
excel-networking.com

## Product drawing




## Standards

| Applicable standard | Detail |
|---|---|
| BS EN 60332-1-2:2004+A11:2016 | Tests on electric and optical fibre cables under fire conditions - Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame |
| IEC 60793-1-1:2022 | Optical fibres - Part 1-1: Measurement methods and test procedures - General and guidance |
| IEC 60793-2:2015 | Optical fibres - Part 2: Product specifications - General |
| IEC 60793-2-10:2017 | Sectional specification for A1 multimode fibres |
| IEC 60793-1-20:2014 | Optical fibres - Part 1-20: Measurement methods and test procedures - Fibre geometry |
| IEC 60793-1-21:2001 | Optical fibres - Part 1-21: Measurement methods and test procedures - Coating geometry |
| IEC 60793-1-22:2001 | Optical fibres - Part 1-22: Measurement methods and test procedures - Length measurement |
| IEC 60793-1-30:2010 | Optical fibres - Part 1-30: Measurement methods and test procedures - Fibre proof test |
| IEC 60793-1-31:2010 | Optical fibres - Part 1-31: Measurement methods and test procedures - Tensile Strength |
| ITU G.651.1 | Characteristics of a 50/125 µm multimode graded index optical fibre cable for the optical access network |



This data sheet was generated at 4:37am 7th November 2026 and is subject to change at any time.

| | |
|---|---|
| EN 50173-1:2018 | Information technology. Generic cabling systems - General requirements |
| EN 50173-2:2007 + A1:2010 | Information technology. Generic cabling systems - Office premises |
| IEC 61754-1:2013 | Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 1: General and guidance |
| IEC 61754-2:1996 | Fibre optic connector interfaces - Part 2: Type BFOC/2,5 connector family |
| IEC 61754-4:2013 | Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 4: Type SC connector family |
| IEC 61754-4-100:2015 | Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 4-100: Type SC connector family - Simplified receptacle SC-PC connector interfaces |
| IEC 61754-20:2012 | Fibre optic connector interfaces - Part 20: Type LC connector family |
| Directive 2011/65/EU (RoHS II) | Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states). |
| Directive (EU) 2015/863 (RoHS III) | Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant. |
| Directive 2008/98/EC (WFD) | Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988). |
| ECHA SCIP Database | Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH. |
| Regulation (EU) 2019/1021 (POPs) | EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355). |
| UK SI 2012 No. 3032 | The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment |

Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

## Part Code Table

| Part Code | Description |
|---|---|
| 204-300 | **Excel Enbeam OM4 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LS0H Aqua 1 m** |
| 204-301 | **Excel Enbeam OM4 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LS0H Aqua 2 m** |
| 204-302 | **Excel Enbeam OM4 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LS0H Aqua 3 m** |
| 204-303 | **Excel Enbeam OM4 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LS0H Aqua 5 m** |
| 204-304 | **Excel Enbeam OM4 Fibre Optic Patch Lead LC-SC Multimode 50/125 DX LS0H Aqua 1 m** |
| 204-305 | **Excel Enbeam OM4 Fibre Optic Patch Lead LC-SC Multimode 50/125 DX LS0H Aqua 2 m** |
| 204-306 | **Excel Enbeam OM4 Fibre Optic Patch Lead LC-SC Multimode 50/125 DX LS0H Aqua 3 m** |
| 204-307 | **Excel Enbeam OM4 Fibre Optic Patch Lead LC-SC Multimode 50/125 DX LS0H Aqua 5 m** |
| 204-308 | **Excel Enbeam OM4 Fibre Optic Patch Lead SC-SC Multimode 50/125 DX LS0H Aqua 1 m** |
| 204-309 | **Excel Enbeam OM4 Fibre Optic Patch Lead SC-SC Multimode 50/125 DX LS0H Aqua 2 m** |
| 204-310 | **Excel Enbeam OM4 Fibre Optic Patch Lead SC-SC Multimode 50/125 DX LS0H Aqua 3 m** |
| 204-323 | **Excel Enbeam OM4 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LS0H Aqua 10 m** |


This data sheet was generated at 4:37am 7th November 2026 and is subject to change at any time.

sales@excel-networking.com
excel-networking.com

| | |
|---|---|
| 204-330 | **Excel Enbeam OM4 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LSOH Violet 1 m** |
| 204-331 | **Excel Enbeam OM4 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LS0H Violet 2 m** |
| 204-332 | **Excel Enbeam OM4 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LS0H Violet 3 m** |
| 204-333 | **Excel Enbeam OM4 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LS0H Violet 5 m** |
| 204-334 | **Excel Enbeam OM4 Fibre Optic Patch Lead LC-SC Multimode 50/125 DX LS0H Violet 1 m** |
| 204-335 | **Excel Enbeam OM4 Fibre Optic Patch Lead LC-SC Multimode 50/125 DX LS0H Violet 2 m** |
| 204-336 | **Excel Enbeam OM4 Fibre Optic Patch Lead LC-SC Multimode 50/125 DX LS0H Violet 3 m** |
| 204-337 | **Excel Enbeam OM4 Fibre Optic Patch Lead LC-SC Multimode 50/125 DX LSOH Violet 5 m** |
| 204-338 | **Excel Enbeam OM4 Fibre Optic Patch Lead SC-SC Multimode 50/125 DX LS0H Violet 1 m** |
| 204-339 | **Excel Enbeam OM4 Fibre Optic Patch Lead SC-SC Multimode 50/125 DX LS0H Violet 2 m** |
| 204-340 | **Excel Enbeam OM4 Fibre Optic Patch Lead SC-SC Multimode 50/125 DX LS0H Violet 3 m** |
| 204-341 | **Excel Enbeam OM4 Fibre Optic Patch Lead SC-SC Multimode 50/125 DX LS0H Violet 5 m** |
| 204-352 | **Excel Enbeam OM4 Fibre Optic Patch Lead LC-LC Multimode 50/125 DX LSOH Violet 10 m** |



This data sheet was generated at 4:37am 7th November 2026 and is subject to change at any time.