
Excel Enbeam Fibre Pigtail OM4 50/125 LC/UPC Violet 2 m

Part Code: 204-350

sales@excel-networking.com
excel-networking.com



Main Features

- Semi Loose Buffered
- Choice of lengths
- Choice of connectors
- Each cable is individually packaged and labelled
- Test Certificate with each cable
- RoHS Compliant

Product Overview

Excel multimode fibre optic pigtails are manufactured from the highest quality 900 micron optical fibre, terminated with ceramic ferrule connectors of various types. To assist in fast cable preparation and splicing semi tight buffered, easy strip, cable is used as standard. Cable preparation, termination and testing is carried out to strictly managed procedures in an Excel approved, ISO9001 registered manufacturing facility.

Each pigtail has a strain relief boot to prolong and maintain performance levels of the assembly. A short distance from the connector a label containing a unique batch number is fixed to cable for quality and traceability purposes.

This data sheet was generated at 3:13am 17th November 2026 and is subject to change at any time.

sales@excel-networking.com
excel-networking.com

Product Specifications

Feature	Values
Fibre type	**Multi mode 50/125**
Category	**OM4**
Length	**2 m**
Type of connector	**LC**
APC-type	**no**
Colour	**Violet**
Strain relief boot	**Push-on**

This data sheet was generated at 3:13am 17th November 2026 and is subject to change at any time.

Product schematics


This data sheet was generated at 3:13am 17th November 2026 and is subject to change at any time.

Excel Enbeam Fibre Pigtail OM4 50/125 LC/UPC Violet 2 m

Part Code: 204-350


sales@excel-networking.com
excel-networking.com

ST



1. ST Dust cover
2. ST connector
3. ST Strain relief boot
4. Easy Strip LSOH cable

SC



1. SC Dust cover
2. SC connector
3. SC Strain relief boot
4. Easy Strip LSOH cable

LC




1. LC Dust cover
2. LC connector
3. LC Strain relief boot
4. Easy Strip LSOH cable

FC




1. FC Dust cover
2. FC connector
3. FC Strain relief boot
4. Easy Strip LSOH cable

Cable Profile



Packaging



This data sheet was generated at 3:13am 17th November 2026 and is subject to change at any time.

Fibre specifications

Features	OM1	OM2	OM3	OM4	OM5
Core diameter	62.5 ± 2.5µm	50 ± 2.5µm	50 ± 2.5µm	50 ± 2.5µm	50 ± 2.5µm
Core Non-circularity	≤5%	≤5%	≤5%	≤5%	≤5%
Core-Cladding Concentricity Error	≤1.5µm	≤1.5µm	≤1.0µm	≤1.0µm	≤1.0µm
Cladding diameter	125 ± 1.0µm	125 ± 1.0µm	125 ± 1.0µm	125 ± 1.0µm	125 ± 0.8µm
Cladding Non-circularity	≤1.0%	≤1.0%	≤1.0%	≤1.0%	≤0.6%
Primary Coating diameter	245 ± 7µm	245 ± 7µm	245 ± 7µm	245 ± 7µm	245 ± 7µm
Coating-Cladding Concentricity Error	≤10.0µm	≤10.0µm	≤10.0µm	≤10.0µm	≤10.0µm
Coating Non-circularity	≤6.0%	≤6.0%	≤6.0%	≤6.0%	≤6.0%
Secondary coating diameter	900 µm nominal	900 µm nominal	900 µm nominal	900 µm nominal	900 µm nominal
Max. attenuation at 850nm	2.7dB/km	2.3dB/km	2.4dB/km	2.4dB/km	2.4dB/km
Max. attenuation at 953nm					1.7dB/km
Max	0.6dB/km	0.6dB/km	0.6dB/km	0.6dB/km	0.6dB/km

This data sheet was generated at 3:13am 17th November 2026 and is subject to change at any time.

attenuation at 1300nm					
Refractive Index at 850nm	**1.496**	**1.482**	**1.482**	**1.482**	**1.482**
Refractive Index at 1300nm	**1.491**	**1.477**	**1.477**	**1.477**	**1.477**
Bandwidth at 850nm	**200 MHz.km**	**500 MHz.km**	**≥1500 MHz.km**	**≥3500 MHz.km**	**≥3500 MHz.km**
Bandwidth at 953nm					**≥1850 MHz.km**
Bandwidth at 1300nm	**500 MHz.km**	**500 MHz.km**	**≥500 MHz.km**	**≥500 MHz.km**	**≥500 MHz.km**
Effective Modal Bandwidth at 850nm			**≥2000 MHz/km**	**≥4700 MHz/km**	**≥4700 MHz/km**
Effective Modal Bandwidth at 953nm					**≥2470 MHz/km**
Numerical Aperture	**0.275 ±0.015**	**0.200 ±0.015**	**0.200 ±0.015**	**0.200 ±0.015**	**0.200 ± 0.015**
Zero Dispersion Wavelength	**1320-1365nm**	**1295-1340nm**	**1295-1340nm**	**1295-1340nm**	**1295-1340nm**
Macrobending Loss - 100 turns, 37.5mm Radius, 850nm	**≤0.50dB**	**≤0.10dB**	**≤0.50dB**	**≤0.50dB**	**≤0.10dB**
Macrobending Loss - 100 turns, 37.5mm Radius,	**≤0.50dB**	**≤0.30dB**	**≤0.50dB**	**≤0.50dB**	**≤0.30dB**

This data sheet was generated at 3:13am 17th November 2026 and is subject to change at any time.

1300nm				
Macrobending Loss - 2 turns, 7.5mm Radius, 850nm	**≤0.2dB**	**≤1.0dB**	**≤1.0dB**	**≤0.2dB**
Macrobending Loss - 2 turns, 7.5mm Radius, 1300nm	**≤0.5dB**	**≤1.0dB**	**≤1.0dB**	**≤0.5dB**

Cable specifications

Features	Values	ST Assemblies	SC Assemblies	LC Assemblies
Construction	**Semi-Tight Buffered**			
No. of Fibres	**1**			
Diameter	**900 micron**			
Temperature range	**-20C to +70C**			
Connector Material		**Nickel plated Brass**	**Composite**	**Composite**
Minimum bend radius	**10 x cable diameter**			
Connector Ferrule		**2.5 mm Zirconium ceramic**	**2.5 mm Zirconium ceramic**	**1.25 mm Zirconium ceramic**
Connector Insertion Loss	**Max. 0.3 dB**			
Connector Return Loss (Multimode)	**Max. -30 dB**			

This data sheet was generated at 3:13am 17th November 2026 and is subject to change at any time.

Ferrule End Face (Singlemode UPC)	**Max. -50 dB**
Ferrule End Face (Singlemode APC)	**Max. -60 dB**

Standards

Applicable standard	Detail
IEC 60793-1-1:2022	Optical fibres - Part 1-1: Measurement methods and test procedures - General and guidance
IEC 60793-2:2015	Optical fibres - Part 2: Product specifications - General
IEC 60793-2-10:2017	Sectional specification for A1 multimode fibres
IEC 60793-1-20:2014	Optical fibres - Part 1-20: Measurement methods and test procedures - Fibre geometry
IEC 60793-1-21:2001	Optical fibres - Part 1-21: Measurement methods and test procedures - Coating geometry
IEC 60793-1-22:2001	Optical fibres - Part 1-22: Measurement methods and test procedures - Length measurement
IEC 60793-1-30:2010	Optical fibres - Part 1-30: Measurement methods and test procedures - Fibre proof test
IEC 60793-1-31:2010	Optical fibres - Part 1-31: Measurement methods and test procedures - Tensile Strength
ITU-T G.651.1:2018	Characteristics of a 50/125 µm multimode graded index optical fibre cable for the optical access network
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
EN 50173-2:2007 + A1:2010	Information technology. Generic cabling systems - Office premises
IEC 61754-1:2013	Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 1:

This data sheet was generated at 3:13am 17th November 2026 and is subject to change at any time.

	General and guidance
IEC 61754-2:1996	Fibre optic connector interfaces - Part 2: Type BFOC/2,5 connector family
IEC 61754-4:2013	Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 4: Type SC connector family
IEC 61754-4-100:2015	Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 4-100: Type SC connector family - Simplified receptacle SC-PC connector interfaces
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
ANSI/TIA 568-3.D	Optical Fiber Cabling and Components Standard
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
UK SI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

This data sheet was generated at 3:13am 17th November 2026 and is subject to change at any time.

sales@excel-networking.com
excel-networking.com

Part Code Table

Part Code	Description
200-552	**Excel Enbeam Fibre Pigtail OM1 62.5/125 SC/UPC Grey 2 m**
200-553	**Excel Enbeam Fibre Pigtail OM2 50/125 SC/UPC White 2 m**
200-555	**Excel Enbeam Fibre Pigtail OM3 50/125 SC/UPC Aqua 2 m**
200-556	**Excel Enbeam Fibre Pigtail OM1 62.5/125 ST/UPC Grey 2 m**
200-557	**Excel Enbeam Fibre Pigtail OM2 50/125 ST/UPC White 2 m**
200-558	**Excel Enbeam Fibre Pigtail OM1 62.5/125 LC/UPC Grey 2 m**
200-559	**Excel Enbeam Fibre Pigtail OM2 50/125 LC/UPC White 2 m**
200-560	**Excel Enbeam Fibre Pigtail OM3 50/125 LC/UPC Aqua 2 m**
200-574	**Excel Enbeam Fibre Pigtail OM2 50/125 ST/UPC Tight Buffered White 2 m**
200-577	**Excel Enbeam Fibre Pigtail OM3 50/125 ST/UPC Aqua 2 m**
200-675	**Excel Enbeam Fibre Pigtail OM5 50/125 SC/UPC Lime Green 2 m**
200-677	**Excel Enbeam Fibre Pigtail OM5 50/125 LC/UPC Lime Green 2 m**
200-677-12	**Excel Enbeam Fibre Pigtail OM5 50/125 LC/UPC Lime Green 2 m (12 Pack)**
204-321	**Excel Enbeam Fibre Pigtail OM4 50/125 SC/UPC Violet 2m**
204-350	**Excel Enbeam Fibre Pigtail OM4 50/125 LC/UPC Violet 2 m**
204-351	**Excel Enbeam Fibre Pigtail OM4 50/125 SC/UPC Violet 2 m**

This data sheet was generated at 3:13am 17th November 2026 and is subject to change at any time.