Excel Enbeam 24 Way Multimode Fibre Optic Panel 24 LC Quad (96 Fibre) Violet

Part Code: 204-553

sales@excel-networking.com
excel-networking.com

CIBSE TM65 Embodied Carbon:



Main Features

- Multiple cable entry to rear
- 1U rack space design
- Special configurations made to order
- Up to 96 fibres
- Optional patchcord management
- 25 year system warranty

Product Overview

The Excel range of LC patch panels are sliding drawer "tray-style" housings suitable for either direct termination or splicing of up to 96 fibres (48 using SC duplex or 96 when using LC quad connections) in a 1U space. Each panel is manufactured from a mix of 1 mm thick steel with a powder-coated finish and a high-density polycarbonate sliding tray, offering a lightweight, strong, durable unit.

To the front of the patch panel, the specified number of duplex/quad adaptors are loaded from left to right. Each panel utilises colour-coded adaptors: beige, aqua and violet for multimode, blue for single mode, and green for single-mode APC.
This design delivers lower emissions and less reliance on mineral extraction, while achieving a 36% decrease in embedded carbon compared with the metal version.

This data sheet was generated at 9:15pm 28th November 2026 and is subject to change at any time.

The lighter construction also minimises floor loading during installation and decreases the overall cabinet weight, improving handling and installation efficiency.
Additional features include easier one-person installation, integrated knockouts, and rear entry points on both the left and right sides for improved cable access and flexibility.

Note that this panel only accepts flangeless SC/LC adaptors and can be assembled to order using a combination of adaptors, pigtails and splice cassettes – call to enquire.

Product Specifications

Feature	Values
Suitable for number of fibre cores	**96**
Suitable for number of module inserts	**24**
Loaded with number of couplings/adapters	**24**
With pigtails	**no**
Fibre type	**Multi mode 50/125**
Fibre class	**OM4/OM3/OM2**
APC-type	**no**
Type of connector external	**LC-Quad**
Type of connector interior	**LC-Quad**
Colour	**Black**
RAL-number	**9005**
Mounting method	**482.6 mm (19 inch) mounting**
Number of rack units (RU)	**1**
Height	**43.5 mm**
Width	**483 mm**
Depth	**219.5 mm**

This data sheet was generated at 9:15pm 28th November 2026 and is subject to change at any time.

Additional specifications

Feature	Value
Operating Temprature	**-40 to +80 °C**
IP Rating	**IP20**
Cable Entry 20mm	**2**
Cable Entry 25mm	**2**
Blown fibre entry	**8**
Material	**Cold rolled steel**
Material Thickness	**1 mm**
Material Coating	**Powder coating**
RoHs Compliant Adaptor	**Yes**
Designed in accordance with	**ISO/IEC 11801, IEC60304,IEC61754, TIA/EIA 568.D**

Included accessories

Accessories	Quantity
Cable Gland (PG 13.5)	**1**
Cable Gland(PG 19)	**1**
Nylon cable tie	**7**
Adjustable cable tie	**4**
24 Position splice holder	**1 to 3 Dependant on fibre count**
Label holder (210 x 9.2 mm)	**2**
Mounting twist tie	**4**


This data sheet was generated at 9:15pm 28th November 2026 and is subject to change at any time.

Cage nuts and screws	**1 pack**

This data sheet was generated at 9:15pm 28th November 2026 and is subject to change at any time.

Product drawings

This data sheet was generated at 9:15pm 28th November 2026 and is subject to change at any time.



This data sheet was generated at 9:15pm 28th November 2026 and is subject to change at any time.

Standards

Applicable standard	Detail
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
UK SI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

Part Code Table

Part Code	Description
200-488	**Excel Enbeam 24 Way Singlemode Fibre Optic Panel 24 LC Quad (96 Fibre) Blue**
200-489	**Excel Enbeam 24 Way Multimode Fibre Optic Panel 24 LC Quad (96 Fibre) Beige**
203-553	**Excel Enbeam 24 Way Multimode Fibre Optic Panel 24 LC Quad (96 Fibre) Aqua**

This data sheet was generated at 9:15pm 28th November 2026 and is subject to change at any time.

sales@excel-networking.com
excel-networking.com

204-553	**Excel Enbeam 24 Way Multimode Fibre Optic Panel 24 LC Quad (96 Fibre) Violet**

This data sheet was generated at 9:15pm 28th November 2026 and is subject to change at any time.