


Excel Enbeam OM3 Armoured CST Fibre Optic Cable Loose Tube 16 Core Eca Blue

excel
without compromise.

Part Code: 205-283

sales@excel-networking.com
excel-networking.com

CIBSE TM65 Embodied Carbon: 0.613 kg CO2e



Main Features

- / Duct grade - rodent resistant
- / UV resistant
- / 25 Year system warranty
- / Sequentially metre marked
- / Cut to length service
- / Euroclass Eca

Product Overview

Excel corrugated steel tape (CST) OM3 50/125 µm armoured loose tube optical fibre cables have been designed specifically for applications requiring a high degree of mechanical protection. These compact, lightweight cables are extremely rugged, provide rodent resistance and are quick and easy to install.

The cables are constructed around a silica gel filled tube(s) containing up to 24 colour coded 250 µm buffered fibres, which is covered with E-glass strength members.

The print legend on the cable now includes information regarding the DOP number, Test and Classification of the cable for traceability.

The CST cable has also been designed for direct burial, to ensure the correct installation a sand back fill must be used at all times.

Excel Enbeam OM3 Armoured CST Fibre Optic Cable Loose Tube 16 Core Eca Blue


Part Code: 205-283

sales@excel-networking.com
excel-networking.com

Product Specifications

Feature	Values
Number of Cores	16
Type of tube	Loose tube
Number of fibres per tube	16
Fibre type	Multi mode 50/125
Category	OM3
Rodent resistant	yes
Outer sheath material	Copolymer, thermoplastic (LSOH)
Outer sheath colour	Blue
Flame retardant according to IEC 60332-1-2	yes
Reaction-to-fire class according to EN 13501-6	Eca
Outer diameter approx.	8.4 mm

Cross-section diagram




Excel Enbeam OM3 Armoured CST Fibre Optic Cable Loose Tube 16 Core Eca Blue

Part Code: 205-283

sales@excel-networking.com
excel-networking.com

Colour coding (as per TIA-598-C)



For fibre core counts above 12 the colour sequence is repeated with the addition of a mark every 70mm for cores 13-24 and two marks for 25-36 and so on.

Cable specifications

Features		Values
Tensile Strength		2000 N
Crush Resistance		3000 N/m
Torsion		± 180°
Temperature performance	Installation	-30°C to +70°C
	Operation	-30°C to +70°C
	Storage	-30°C to +70°C
Loose tubes	Number	1
	Material	PBT
Loose Tube ID/OD	4-16 Cores	2.0/2.8 ± 0.1 mm
	24 Cores	2.6/3.5 ± 0.1 mm
Peripheral Strength Member		Glass Yarn + WS Yarn
Armoring	Thickness	0.150 mm
	Material	ECCS Tape
Outer Sheath	Thickness	1.8 mm (Nominal)

Excel Enbeam OM3 Armoured CST Fibre Optic Cable Loose Tube 16 Core Eca Blue

Part Code: 205-283

sales@excel-networking.com
excel-networking.com

	Material	LSZH
Ripcord	Number	1
	Material	Polyester
Overall Cable Diameter	4-16 Cores	8.4 ± 0.5 mm
	24 Cores	9.2 ± 0.5 mm
Cable Weight	4-16 Cores	100.0 ± 10 kg/km
	24 Cores	115 ± 10 kg/km
Bending Radius	Short term	20 x Diameter
	Long term	10 x Diameter

Fibre specifications

Features		OM1	OM2	OM3	OM4
Attenuation	@850 nm	≤ 3.0 dB/km	≤ 2.7 dB/km	≤ 2.7 dB/km	≤ 2.7 dB/km
	@1300 nm	≤ 1.0 dB/km	≤ 0.8 dB/km	≤ 0.8 dB/km	≤ 0.8 dB/km
Bandwidth	@850 nm	≥ 200 MHz.km	≥ 500 MHz.km	≥ 1500 MHz.km	≥ 3500 MHz.km
	@1300 nm	≥ 600 MHz.km	≥ 550 MHz.km	≥ 500 MHz.km	≥ 500 MHz.km
Core Diameter		62.5 ± 2.5 μm	50 ± 2.5 μm	50 ± 2.5 μm	50 ± 2.5 μm
Core Cladding Concentricity Error		≤ 1 μm	≤ 1 μm	≤ 1 μm	≤ 1 μm
Cladding Diameter		125 ± 1 μm	125 ± 1 μm	125 ± 1 μm	125 ± 1 μm

Excel Enbeam OM3 Armoured CST Fibre Optic Cable Loose Tube 16 Core Eca Blue

Part Code: 205-283

sales@excel-networking.com
excel-networking.com

Cladding Non-circularity	≤ 1 %	≤ 1 %	≤ 1 %	≤ 1 %
Coating Diameter (Coloured)	250 ± 15 µm	250 ± 15 µm	250 ± 15 µm	250 ± 15 µm

Standards

Applicable Standard	Subject
IEC 60332-1-2:2004	Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame
IEC 60754-2:2011	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity
IEC 61034-2:2005+A1:2013	Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements
IEC 60793-1-1:2022	Optical fibres - Part 1-1: Measurement methods and test procedures - General and guidance
IEC 60793-2-10:2017	Sectional specification for A1 multimode fibres
IEC 60793-1-20:2014	Optical fibres - Part 1-20: Measurement methods and test procedures - Fibre geometry
IEC 60793-1-21:2001	Optical fibres - Part 1-21: Measurement methods and test procedures - Coating geometry
IEC 60793-1-22:2001	Optical fibres - Part 1-22: Measurement methods and test procedures - Length measurement
IEC 60793-1-30:2010	Optical fibres - Part 1-30: Measurement methods and test procedures - Fibre proof test
IEC 60793-1-41:2010	Optical fibres - Part 1-41: Measurement methods and test procedures – Bandwidth

Excel Enbeam OM3 Armoured CST Fibre Optic Cable Loose Tube 16 Core Eca Blue

Part Code: 205-283

sales@excel-networking.com
excel-networking.com

ITU G.651.1	Characteristics of a 50/125 µm multimode graded index optical fibre cable for the optical access network
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
EN 50575:2014 + A1: 2016	Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements
EN 50399:2011+A1:2016	Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
ANSI/TIA 568-3.D	Optical Fiber Cabling and Components Standard
ANSI/TIA/EIA 598-D	Optical Fibre Cable Colour Coding
IEC 60794-1-2/F5	Generic specification – Optical fibre cable test procedures – Bending test (Method F5)
IEC 60794-1-205	Optical fibre cables – Part 1-205: Generic specification – Basic optical cable test procedures – Water penetration test
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates

Excel Enbeam OM3 Armoured CST Fibre Optic Cable Loose Tube 16 Core Eca Blue

Part Code: 205-283

sales@excel-networking.com
excel-networking.com

(DEHP, BBP, DBP, DIBP) to Annex II — compliant.

UKSI 2012 No. 3032

The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

Part Code Table

Part Code	Description
205-280	Excel Enbeam OM3 Armoured CST Fibre Optic Cable Loose Tube 4 Core Eca Blue
205-281	Excel Enbeam OM3 Armoured CST Fibre Optic Cable Loose Tube 8 Core Eca Blue
205-282	Excel Enbeam OM3 Armoured CST Fibre Optic Cable Loose Tube 12 Core Eca Blue
205-283	Excel Enbeam OM3 Armoured CST Fibre Optic Cable Loose Tube 16 Core Eca Blue
205-284	Excel Enbeam OM3 Armoured CST Fibre Optic Cable Loose Tube 24 Core Eca Blue