Excel Enbeam OS2 FTTx Drop Cable 250 μm 4 Core Cca White

Item Code: 205-331









ズ G.657.A2 Bend Insensitive
X Small Diameter Pre-terminated options
X Ideal for FTTx/PON Applications
X 250 micron fibre
X Euroclass Cca-s1b-d0-a1
X 25 Year system warranty
X CIBSE TM65 Embodied Carbon: 0.049 kg CO2e

Product Overview

Enbeam OS2 Singlemode FTTx Drop Cable 250 μ m 4 Core 9/125 Cca White, part of a huge range of OS2 fibre optic cables fully stocked at Mayflex.

The Enbeam from 2 to 4-core mini breakout/drop cable is designed for indoor FTTx applications.

The very small diameter, high strength and CPR compliance to Cca, coupled with bend-insensitive fibres makes this cable ideal for behind-the-wall installations in any FTTx or PON network, especially where space is tight.

The cable can be supplied on reels or pre-cut lengths as well as pre-terminated on one end into an outlet box.

Product Specifications

Feature	Values
Number of Cores	4
Number of fibres per tube	4
Fibre type	Single mode 9/125
Category	OS2
Rodent resistant	yes
Outer sheath colour	White
Longitudinal water blocking cable	no

Excel Enbeam OS2 FTTx Drop Cable 250 μm 4 Core Cca White

Item Code: 205-331



Flame retardant according to IEC 60332-1-2	yes
Low smoke (acc. IEC 61034-2)	yes
Reaction-to-fire class according to EN 13501-6	Cca
Smoke development class according to EN 13501-6	slb
Euro class flaming droplets/particles according to EN 13501-6	d0
Euro class acidity according to EN 13501-6	al
Outer diameter approx.	3 mm
RAL-number	9010

Part Number Table

Part Number	Description
205-331	Excel Enbeam OS2 FTTx Drop Cable 250 ?m 4 Core Cca White
205-332	Excel Enbeam OS2 FTTx Drop Cable 250 ?m 2 Core Cca White

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

