



✗ Duct grade - rodent resistant

✗ Sequentially metre marked

✗ UV Resistant

✗ Cut to length service

✗ 25 Year system warranty

✗ Euroclass Eca

## Product Overview

Excel steel wire (SWA) OM2 50/125 $\mu$ m armoured loose tube optical fibre cables have been designed specifically for direct burial and the most demanding of installations.

These cables are constructed from standard single loose tube cables which are then packed into a flexible but strong fibreglass water blocking strength member. An internal sheath of material is then applied, a rip cord is inserted under this sheath to ease cable stripping. Lengths of steel wire armouring are then applied and an oversheath is added.

The print legend on the cable now includes information regarding the DOP number, Test and Classification of the cable for traceability.

## Product Specifications

Feature	Values
Number of Cores	4
Type of tube	Loose tube
Number of fibres per tube	4
Fibre type	Multi mode 50/125
Category	OM2
Rodent resistant	yes
Outer sheath material	Copolymer, thermoplastic (LSOH)
Outer sheath colour	Black

Flame retardant according to IEC 60332-1-2 yes

Reaction-to-fire class according to EN 13501-6 Eca

Outer diameter approx. 10.5 mm

### Cable specifications

Features	Values
Tensile Strength	3000 N
Crush Resistance	1500 N/m
Torsion	± 180 °
Temperature performance	<p>Installation -30°C to +70°C</p> <p>Operation -30°C to +70°C</p> <p>Storage -30°C to +70°C</p>
Loose tubes	<p>Number 1</p> <p>Material PBT</p>
Loose Tube ID/OD	<p>4-16 Cores 2.2/3.2 ± 0.1 mm</p> <p>24 Cores 2.6/3.5 ± 0.1 mm</p>
Peripheral Strength Member	Glass Yarn
Armoring	<p>Thickness 0.8 mm</p> <p>Material Soft Zinc Coated Steel Wires</p>
Outer Sheath	<p>Thickness 1.4 mm (Nominal)</p> <p>Material LSZH</p>
Ripcord	<p>Number 3</p> <p>Material Polyester</p>
Overall Cable Diameter	<p>4-16 Cores 10.0 ± 0.5 mm</p> <p>24 Cores 10.5 ± 0.5 mm</p>
Cable Weight	<p>4-16 Cores 165 ± 15 kg/km</p> <p>24 Cores 180 ± 15 kg/km</p>
Bending Radius	<p>Short term 20 x Diameter</p> <p>Long term 10 x Diameter</p>

### Fibre specifications

Features	OM1	OM2
Attenuation	@850 nm	$\leq 3.0 \text{ dB/km}$
	@1300 nm	$\leq 1.0 \text{ dB/km}$
Bandwidth	@850 nm	$\geq 200 \text{ MHz.km}$
	@1300 nm	$\geq 600 \text{ MHz.km}$
Core Diameter	$62.5 \pm 2.5 \mu\text{m}$	$50 \pm 2.5 \mu\text{m}$
Core Cladding Concentricity Error	$\leq 1 \mu\text{m}$	$\leq 1 \mu\text{m}$
Cladding Diameter	$125 \pm 1 \mu\text{m}$	$125 \pm 1 \mu\text{m}$
Cladding Non-circularity	$\leq 1 \%$	$\leq 1 \%$
Coating Diameter (Coloured)	$250 \pm 15 \mu\text{m}$	$250 \pm 15 \mu\text{m}$

### Standards

Applicable Standard	Subject
IEC 60332-1-2:2004	Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame
IEC 60754-2:2011	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity
IEC 61034-2:2005+A1:2013	Measurement of smoke density of cables burning under defined conditions - Part 2: Test procedure and requirements
IEC 60793-1-1:2022	Optical fibres - Part 1-1: Measurement methods and test procedures - General and guidance
IEC 60793-2-10:2017	Sectional specification for A1 multimode fibres
IEC 60793-1-20:2014	Optical fibres - Part 1-20: Measurement methods and test procedures - Fibre geometry
IEC 60793-1-21:2001	Optical fibres - Part 1-21: Measurement methods and test procedures - Coating geometry
IEC 60793-1-22:2001	Optical fibres - Part 1-22: Measurement methods and test procedures - Length measurement
IEC 60793-1-30:2010	Optical fibres - Part 1-30: Measurement methods and test procedures - Fibre proof test

IEC 60793-1-41:2010	Optical fibres - Part 1-41: Measurement methods and test procedures - Bandwidth
ITU G.651.1	Characteristics of a 50/125 µm multimode graded index optical fibre cable for the optical access network
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
EN 50575: 2014 + A1: 2016	Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements
EN 50399:2011+A1:2016	Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
ANSI/TIA 568-3.D	Optical Fiber Cabling and Components Standard
ANSI/TIA/EIA 598-D	Optical Fibre Cable Colour Coding
IEC 60794-1-2/F5	Generic specification - Optical fibre cable test procedures - Bending test (Method F5)
RoHS-II/-III (2011/65/EU & 2015/863): 2023	Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).
WFD: 2023	Compliant to Waste Framework Directive
SCIP: 2023	Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
POPs (EU) No 2019/1021	EU Regulation for the restriction of Persistent Organic Pollutants.

### Part Number Table

Part Number	Description
205-348	Excel Enbeam OM2 SWA Direct Burial Fibre Optic Cable Loose Tube 4 Core Eca Black
205-352	Excel Enbeam OM2 SWA Armoured Fibre Optic Cable Loose Tube 12 Core Eca Black
205-354	Excel Enbeam OM2 SWA Armoured Fibre Optic Cable Loose Tube 24 Core Eca Black
205-364	Excel Enbeam OM2 SWA Direct Burial Fibre Optic Cable Loose Tube 8 Core Eca Black

Excel Enbeam OM2 SWA Direct Burial Fibre Optic  
Cable Loose Tube 4 Core Eca Black

Item Code: 205-348



205-366

Excel Enbeam OM2 SWA Armoured Fibre Optic Cable Loose Tube 16 Core Eca  
Black

Excel is a world class premium performing end to end infrastructure solution designed,  
Manufactured, supported and delivered without compromise.

Contact us at [sales@excel-networking.com](mailto:sales@excel-networking.com)

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.

