Excel Enbeam OM3 SWA Direct Burial Fibre Optic Cable Loose Tube 4 Core Eca Black

Part Code: 205-376

sales@excel-networking.com
excel-networking.com

CIBSE TM65 Embodied Carbon: 1.235 kg CO2e



Main Features

- / Water Resistant & UV Resistant
- / Sequentially metre marked
- / Euroclass: Eca
- / Duct grade Rodent resistant
- / Cut to length service
- / 25 Year system warranty

Product Overview

Enbeam OM3 Multimode SWA Direct Burial Fibre Optic Cable Loose Tube 4 Core 50/125 Eca Black.
Excel steel wire (SWA) OM3 50/125 µm armoured loose tube optical fibre cables have been designed specifically for direct burial and the most demanding of installations.

These cables are constructed from standard single loose tube cables which are then packed into a flexible but strong fibreglass water blocking strength member.

An internal sheath with a rip cord is inserted with lengths of steel wire armouring over the top and then an oversheath is added providing a strong but flexible cable assembly.


This data sheet was generated at 4:45am 26th November 2026 and is subject to change at any time.

sales@excel-networking.com
excel-networking.com

Product Specifications

Feature	Values
Number of Cores	**4**
Type of tube	**Loose tube**
Number of fibres per tube	**4**
Fibre type	**Multi mode 50/125**
Category	**OM3**
Rodent resistant	**yes**
Outer sheath material	**Copolymer, thermoplastic (LS0H)**
Outer sheath colour	**Black**
Reaction-to-fire class according to EN 13501-6	**Eca**
Outer diameter approx.	**10.5 mm**

Cross-section diagram



This data sheet was generated at 4:45am 26th November 2026 and is subject to change at any time.

Cable specifications

Features	Values	
Tensile Strength		**3000N**
Crush Resistance		**1500N/m**
Torsion		
Temperature performance	**Installation**	**-30^{0}C to +70^{0}C**
	Operation	**-30^{0}C to +70^{0}C**
	Storage	**-30^{0}C to +70^{0}C**
Loose tubes		
Loose Tube ID/OD		
Peripheral Strength Member		
Armoring	**Thickness**	**0.8 mm**
	Material	**Soft Zinc Coated Steel Wires**
Outer Sheath	**Thickness**	**1.4 mm (Nominal)**
	Material	**LSZH**
Ripcord	**Number**	**3**
	Material	**Polyester**
Bending Radius	**Short term**	**20 x Diameter**
	Long term	
Attenuation	**@850nm**	**≤ 3.0 dB/km**
	@1300 nm	
Core Cladding Concentricity Error		
Cladding Diameter		
Cladding Non-circularity		

This data sheet was generated at 4:45am 26th November 2026 and is subject to change at any time.

Coating Diameter	

Standards

Applicable Standard	Subject
IEC 60332-1-2:2004	Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame
IEC 60754-2:2014+A1:2020	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity
IEC 61034-2:2005+A2:2020	Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements
IEC 60793-1-1:2022	Optical fibres - Part 1-1: Measurement methods and test procedures - General and guidance
IEC 60793-1-20:2014	Optical fibres - Part 1-20: Measurement methods and test procedures - Fibre geometry
IEC 60793-1-21:2001	Optical fibres - Part 1-21: Measurement methods and test procedures - Coating geometry
IEC 60793-1-22:2001	Optical fibres - Part 1-22: Measurement methods and test procedures - Length measurement
IEC 60793-1-30:2010	Optical fibres - Part 1-30: Measurement methods and test procedures - Fibre proof test
ITU G.652.D	Characteristics of a single-mode optical fibre and cable
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
EN 50575: 2014 + A1: 2016	Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements

This data sheet was generated at 4:45am 26th November 2026 and is subject to change at any time.

EN 50399:2011+A1:2016	Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
ANSI/TIA 568-3.D	Optical Fiber Cabling and Components Standard
ANSI/TIA/EIA 598-D	Optical Fibre Cable Colour Coding
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
UK SI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

This data sheet was generated at 4:45am 26th November 2026 and is subject to change at any time.

sales@excel-networking.com
excel-networking.com

Part Code Table

Part Code	Description
205-376	**Excel Enbeam OM3 SWA Direct Burial Fibre Optic Cable Loose Tube 4 Core Eca Black**
205-377	**Excel Enbeam OM3 SWA Direct Burial Fibre Optic Cable Loose Tube 8 Core Eca Black**
205-378	**Excel Enbeam OM3 SWA Direct Burial Fibre Optic Cable Loose Tube 12 Core Eca Black**

This data sheet was generated at 4:45am 26th November 2026 and is subject to change at any time.