Excel Encasa OS2 Multi Dwelling Drop Cable with 12 SCA Adaptors and 12 Core SCA to LCA 60 m

Part Code: 207-290-60

sales@excel-networking.com
excel-networking.com

CIBSE TM65 Embodied Carbon: 14.028 kg CO2e



Main Features

- / Suitable for internal/external
- / UL94-V0 compliant
- / Euroclass Cca-s1b,d0,a1
- / Pre-loaded drop cable
- / Integrated fibre management
- / CIBSE TM65 Embodied Carbon: 14.028 kg CO2e

Product Overview

The Excel Encasa IP56 multi dwelling unit has been designed for use within an internal riser application, fitted with a Cca grade internal 12 core SCA to LCA drop cable allowing quick deployment and connectivity.

Product Specifications

Feature	Values

This data sheet was generated at 11:10pm 21st November 2026 and is subject to change at any time.

Surface mounted	**yes**
Type of connector	**LCA**
With couplers	**yes**
Suitable for number of couplers	**24**
Suitable for type of fibre	**Single mode**
IP-rating	**IP65**
Ambient temperature	**-40...60 °C**
Width	**275 mm**
Height	**330 mm**
Depth	**101 mm**

Additional specifications

Features		Values
Insertion loss	**LCA @1310nm**	**≤0.3db**
	SCA @1310nm	**≤0.3db**
Return loss	**MTP @1310nm**	**>65db**
	SCA @1310nm	**>65db**
Maximum tensile strength (N)	**Short term**	**150**
	Long term	**80**
Minimum bend radius (mm)	**Dynamic**	**30 x diameter**
	Static	**15 x diameter**
Maximum cruish resistance(N/100mm2)		**500**
Maximum attenuation	**@ Full spectrum**	**≤0.4dB/km**

This data sheet was generated at 11:10pm 21st November 2026 and is subject to change at any time.


sales@excel-networking.com
excel-networking.com

Dispersion coefficent	**@1310nm**	**≤3.0ps//(nm.km)**
	@1550nm	**≤18ps//(nm.km)**
Durability		**500 matings**
Fibre type		**G.657.A2**
Outer jacket material		**LSZH**
Outer diameter		**3mm**
Operational temperature		**-20 to +70 °C**

This data sheet was generated at 11:10pm 21st November 2026 and is subject to change at any time.

sales@excel-networking.com
excel-networking.com

Product drawings



Standards

Applicable standard	Detail
IEC 60332-1-2:2004	Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame
IEC 60754-2:2014+A1:2020	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity
IEC 61034-2:2005+A2:2020	Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements

This data sheet was generated at 11:10pm 21st November 2026 and is subject to change at any time.

IEC 60793-1-1:2022	Optical fibres - Part 1-1: Measurement methods and test procedures - General and guidance
IEC 60793-1-20:2014	Optical fibres - Part 1-20: Measurement methods and test procedures - Fibre geometry
IEC 60793-1-21:2001	Optical fibres - Part 1-21: Measurement methods and test procedures - Coating geometry
IEC 60793-1-22:2001	Optical fibres - Part 1-22: Measurement methods and test procedures - Length measurement
IEC 60793-1-30:2010	Optical fibres - Part 1-30: Measurement methods and test procedures - Fibre proof test
ITU G.652.D	Characteristics of a single-mode optical fibre and cable
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
EN 50575: 2014 + A1:2016	Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements
EN 50399:2011+A1:2016	Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
ANSI/TIA 568-3.D	Optical Fiber Cabling and Components Standard
ANSI/TIA/EIA 598-D	Optical Fibre Cable Colour Coding
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances

This data sheet was generated at 11:10pm 21st November 2026 and is subject to change at any time.

	of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
UK SI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

Part Code Table

Part Code	Description
207-290-30	**Excel Encasa OS2 Multi Dwelling Drop Cable with 12 SCA Adaptors and 12 Core SCA to LCA 30 m**
207-290-40	**Excel Encasa OS2 Multi Dwelling Drop Cable with 12 SCA Adaptors and 12 Core SCA to LCA 40 m**
207-290-50	**Excel Encasa OS2 Multi Dwelling Drop Cable with 12 SCA Adaptors and 12 Core SCA to LCA 50 m**
207-290-60	**Excel Encasa OS2 Multi Dwelling Drop Cable with 12 SCA Adaptors and 12 Core SCA to LCA 60 m**
207-290-75	**Excel Encasa OS2 Multi Dwelling Drop Cable with 12 SCA Adaptors and 12 Core SCA to LCA 75 m**

This data sheet was generated at 11:10pm 21st November 2026 and is subject to change at any time.