Excel Enbeam HD 6P-12F-LC-OM3 Cassette Loaded with Quad LC Adaptors

Item Code: 208-106









- X High Density 12 fibre LC cassette
- X Complete with splice protectors
- X Can be spliced or direct terminated
- X Pre-termination options
- X OS2, OM3 and OM4 options
- X 25 Year System Warranty Available

Product Overview

The Excel LC High-Density cassette is designed for the Excel HD 1U panel, which has a capacity for 12 cassettes, offering up to 144 fibres per 1U. A range of cassettes are offered and can be mixed and matched as required to offer a highly dense and flexible system for both LC and MTP connectivity.

The LC cassettes can be spliced (12 magnetic splice protectors are included), direct terminated or pre-terminated offering a truly plugn-play solution. The cassettes can be supplied with or without pigtails. See the part number table below for all options. The pigtails (if supplied) are 12-colours and loaded to TIA 598 colour standard.

The cassettes can be inserted into the panel from the front or the rear and feature 2 physical stops, one installed and one for patching.

The panel also offers full and innovative patchcord management to the front and cable management to the rear.

Product Specifications

Feature	Values
Suitable for number of fibre cores	12
With coupling/adapter	yes
Type of connector external	LC
Type of connector interior	LC
Fibre type	Multi mode
APC-type	no
Colour	Grey

Excel Enbeam HD 6P-12F-LC-OM3 Cassette Loaded with Quad LC Adaptors


Item Code: 208-106



Additional specifications

Features	Values
Operating Temprature	-40 to +80 °C
Capacity	12 LC-Fibres per cassette
Width	108mm
Height	12.5mm
Depth	232mm
Material Coating	ABS UL94-V0
Colour	Grey

Product drawing



Excel Enbeam HD 6P-12F-LC-OM3 Cassette Loaded with Quad LC Adaptors

Item Code: 208-106



Standards

Applicable standard	Detail
RoHS-II/-III (2011/65/EU & 2015/863): 2023	Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).
IEC 61754-1:2013	Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 1: General and guidance
WFD: 2023	Compliant to Waste Framework Directive
SCIP: 2023	Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
POPs (EU) No 2019/1021	EU Regulation for the restriction of Persistent Organic Pollutants.

Part Number Table

Part Number	Description
208-105	Excel Enbeam HD 6P-12F-LC-OS2 Cassette Loaded with Quad LC Adaptors
208-106	Excel Enbeam HD 6P-12F-LC-OM3 Cassette Loaded with Quad LC Adaptors
208-107	Excel Enbeam HD 6P-12F-LC-OM4 Cassette Loaded with Quad LC Adaptors
208-108	Excel Enbeam HD 6P-12F-LC-OS2 Cassette Loaded with Quad Adaptors $\&$ Pigtails
208-109	Excel Enbeam HD 6P-12F-LC-OM3 Cassette Loaded with Quad Adaptors $\&$ Pigtails
208-110	Excel Enbeam HD 6P-12F-LC-OM4 Cassette Loaded with Quad Adaptors & Pigtails

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.