
Excel Enbeam HD 4P MTP Coupler Cassette Key Up/Key Down Singlemode

Part Code: 208-116

sales@excel-networking.com
excel-networking.com



Main Features

- / High Density 4-port MTP Coupler Module
- / Houses 4 MTP Couplers
- / Key-Aligned and Key-Up/Key-Down Adaptor options
- / Density up to 576 fibres in 1U when fully loaded
- / Up to 1152 fibres in 1U with 24-fibre MTP's
- / Part of the Excel HD panel system

Product Overview

The Excel LC-MTP High-Density 4-Port through-coupler module is designed for the Excel HD 1U panel, which has a capacity for 12 modules, offering up to 576 fibres per 1U (12-way MTP) or 1152 fibres per 1U (24-way MTP).
The MTP Modules can be mixed and matched with other cassettes within the range to offer a highly flexible patching solution.

Two versions are available – The Multimode version features Aligned-Key adaptors, whilst the Singlemode version supports angled MTP and offers Key-Up/Key-Down Adaptors.

The Modules can be inserted into the panel from the front or the rear and feature 2 physical stops, one installed and one for patching.

The panel also offers full and innovative patch cord management to the front and cable management to the rear.

This data sheet was generated at 12:31pm 25th November 2026 and is subject to change at any time.

Product Specifications


Feature	Values
Suitable for number of fibre cores	**48/96**
With coupling/adapter	**yes**
Type of connector external	**MT/MPO**
Type of connector interior	**MT/MPO**
Fibre type	**Single mode**
APC-type	**no**
Colour	**Grey**

Additional specifications

Features	Values
Number of MTP	**4**
Width	**109mm**
Height	**12.7mm**
Depth	**102mm**
Material	**ABS UL94-V0**
Colour	**Grey**
Operating temprature	**-40 to +80 °C**

This data sheet was generated at 12:31pm 25th November 2026 and is subject to change at any time.

Product drawing



Standards

Applicable standard	Detail
IEC 61754-1:2013	Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 1: General and guidance
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and

This data sheet was generated at 12:31pm 25th November 2026 and is subject to change at any time.

	UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
UK SI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

Part Code Table

Part Code	Description
208-114	**Excel Enbeam HD 4P MTP Coupler Cassette Aligned Key Multimode**
208-116	**Excel Enbeam HD 4P MTP Coupler Cassette Key Up/Key Down Singlemode**

This data sheet was generated at 12:31pm 25th November 2026 and is subject to change at any time.