# Item Code: 208-140







### **Product Overview**

The Excel Enbeam 1U 19" HD panel provides an expandable and innovative cassette based patching solution. Each panel has a maximum capacity of 12 cassettes, which are snapped into position quickly, easily and without tooling. Once in position the cassette can be moved back and forth via the sliding drawer mechanism. LC presentation cassettes contain 24 fibres, enabling up to 288 cores to be terminated/patched in 2U of rack space. A variety of cassettes are offered providing a highly flexible system and all cassettes can be mixed and matched as required.

Options include LC splice cassettes, LC-MTP cassettes and MTP pass-through cassettes (offering up to 3456 fibres in 2U using standard 12 core Excelerator trunk cables). LC cassettes are offered with singlemode (blue), OM3 (aqua) or OM4 (violet) adaptors. The cassettes can be spliced or pre-terminated. The panel also offers full and innovative patchcord management to the front and cable management to the rear.

### **Product Specifications**

FeatureValuesSuitable for number of fibre cores288Suitable for number of module inserts12With front plateyesWith housingyesType of connector externalLCType of connector interiorLCColourBlackRAL-number9005		
Suitable for number of module inserts12With front plateyesWith housingyesType of connector externalLCType of connector interiorLCColourBlack	Feature	Values
With front plateyesWith housingyesType of connector externalLCType of connector interiorLCColourBlack	Suitable for number of fibre cores	288
With housing yes   Type of connector external LC   Type of connector interior LC   Colour Black	Suitable for number of module inserts	12
Type of connector external LC   Type of connector interior LC   Colour Black	With front plate	yes
Type of connector interior LC   Colour Black	With housing	yes
Colour Black	Type of connector external	LC
	Type of connector interior	LC
RAL-number 9005	Colour	Black
	RAL-number	9005






Mounting method	482.6 mm (19 inch) mounting
Number of rack units (RU)	2
Height	87 mm
Width	482 mm
Depth	400 mm


# Additional specifications

Features	Values
Number of Modules	12
IP rating	IP20
Material	Cold rolled steel
Material thickness	1.2mm
Material coating	Powder Coating
Operating temprature	-20 to +85 °C





# **Product drawing**



### Standards

Applicable standard	Detail
RoHS-II/-III (2011/65/EU & 2015/863): 2023	Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).
IEC 61754-1:2013	Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 1: General and guidance
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
WFD: 2023	Compliant to Waste Framework Directive
SCIP: 2023	Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
POPs (EU) No 2019/1021	EU Regulation for the restriction of Persistent Organic Pollutants.



## **Part Number Table**

### Part Number

208-140

Description

Excel Enbeam 2U 288C HD Cassette Fibre Optic Panel

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.