


Excel Enbeam 2 Way External 18/14 mm Blowing Tube Green

excel
without compromise.

Part Code: 208-787

sales@excel-networking.com
excel-networking.com



Main Features

- / Direct-bury
- / Multiple sizes available
- / Crush and impact resistant
- / HDPE sheath
- / Multiple bundle configurations
- / RoHS Compliant

Product Overview

Enbeam direct bury blowing tubes have been designed for direct burial to allow blown fibre to be distributed externally where there are no existing ducts available. All tube bundles are over-sheathed with High Density Polyethylene (HDPE) to withstand the friction when installing the micro ducts. All internal tubes are colour coded for easy identification and have a low friction inner coating to reduce drag & maximise blowing distances and have a thicker internal wall to withstand the environment when direct buried.

Tubes are easily broken out of the main sheath and can be branched-off using the Enbeam push-fit blown tube connectors. The tubes are supplied on disposable wooden drums and capped at both ends to prevent ingress of moisture or contamination.

Part Code: 208-787

sales@excel-networking.com
excel-networking.com

Product Specifications

| Feature | Values |
|-----------------------------------|--------|
| Suitable for outdoor installation | yes |
| Halogen free | no |
| Outer sheath colour | Green |

Additional specifications

| Features | Values |
|----------------------------|-------------------------------------|
| Sheath material | HDPE |
| Pressure | burst blowing |
| | min. 35 bar 12 bar (recommended) |
| Recommended cable diameter | 4.2-9.8mm |

Additional specifications

| Features | 1x18/14 | 2x18/14 | 4x18/14 |
|-----------------------------|-------------|---------|---------|
| MAX (mm) | | 37.5 | 45.5 |
| MIN (mm) | | 19.5 | 37.5 |
| Outer diameter (OD) | 18±0.1mm | | |
| Inner diameter (ID) | min. 13.9mm | | |
| Ovality | max 5% | | |
| Sheath thickness (mm) | 4 | 0.75 | 0.75 |
| Installation tensile force, | 1810 N | 3620 N | 7240 N |


Excel Enbeam 2 Way External 18/14 mm Blowing Tube Green

Part Code: 208-787

sales@excel-networking.com
excel-networking.com

| max | | | |
|--------------------------------------|-----------------------|-----------------------|-----------------------|
| Min. bending radius \perp MAX (mm) | 180 | 195 | 455 |
| Min. bending radius \perp MIN (mm) | N/A | 375 | 375 |
| Weight (kg/km) | 96 | 270 | 487 |
| Operating temperatures | -40°C to +70°C | -40°C to +70°C | -40°C to +70°C |
| Transport/storage temperatures | -40°C to +70°C | -40°C to +70°C | -40°C to +70°C |
| Installation temperatures | -10°C to +50°C | -10°C to +50°C | -10°C to +50°C |

Product drawing



Standards

| Applicable standard | Detail |
|-------------------------------|---|
| EN ISO 291:2008 | Plastics – Standard atmospheres for conditioning and testing |
| EN ISO 2505:2005 | Thermoplastics pipes – Longitudinal reversion – Test method |
| ČSN 010254:1976 | Sampling inspection by attributes |
| EN ISO 1167-1:2006 | Thermoplastics pipes, fittings and assemblies for the conveyance of fluids – Determination of the resistance to internal pressure |
| EN 12201-1:2011 | Plastics piping systems for water supply, and for drainage and sewerage under pressure – PE |
| EN 12201-2:2011+A1:2013 | Plastics piping systems for water supply, and for drainage and sewerage under pressure – Polyethylene (PE) – Part 2: Pipes |
| EN ISO 3127:2017 | Plastics piping and ducting systems – Thermoplastics pipes – Test method for resistance to external blows by the round-the-clock method |
| IEC 60 794-1-1:2015 | Optical fibre cables – Part 1-1: Generic specification – General |
| IEC 60 794-1-2:2017 | Optical fibre cables – Part 1-2: Generic specification – Basic optical cable test procedures – General guidance |
| IEC 60794-1-21:2015+AMD1:2020 | Optical fibre cables – Part 1-21: Generic specification – Basic optical cable test procedures – Mechanical tests methods |
| IEC 60 794-1-22:2017 | Optical fibre cables – Part 1-22: Generic specification – Basic optical cable test procedures – Environmental tests methods |
| IEC 60 794-1-23:2019 | Optical fibre cables – Part 1-23: Generic specification – Basic optical cable test procedures – Cable element test methods |
| EN IEC 60 794-1-24:2014 | Optical fibre cables – Part 1-24: Generic specification – |

Excel Enbeam 2 Way External 18/14 mm Blowing Tube Green

Part Code: 208-787

sales@excel-networking.com
excel-networking.com

| | |
|---------------------------|---|
| | Basic optical cable test procedures – Electrical test methods |
| IEC 60 794-2:2017 | Optical fibre cables – Part 2: Indoor cables – Sectional specification |
| ASTM D 1894-14 | Standard Test Method for Static and Kinetic Coefficient of Friction of Plastic Film and Sheeting |
| ASTM D2122-16 | Standard Test Method for Determining Dimensions of Thermoplastic Pipe and Fittings |
| EN 13501-1:2018 | Fire classification of construction products and building elements – Part 1: Classification using data from reaction to fire tests |
| ISO 6259-1,2,3:1997-2015 | Thermoplastic pipes – Determination of tensile properties |
| ISO 3126:2005 | Plastics piping systems – Plastics components – Determination of dimensions |
| ISO 527-1:2019 | Plastics – determination of tensile properties – Part 1: General principles |
| ISO 1133-1:2011 | Determination of the melt mass-flow rate (MFR) and the melt volume-flow rate (MVR) of thermoplastics |
| EN 61386-24:2010 | Conduit systems for cable management – Part 24: Particular requirements – Conduit systems buried underground. |
| ISO 1183-1:2019 | Plastics – Methods for determining the density of non-cellular plastics – Part 1: Immersion method, liquid pycnometer method and titration method |
| ISO 1183-2:2019 | Part 2: Density gradient column method |
| ISO 6964:2019 | Polyolefin pipes and fittings – Determination of carbon black content by calcination and pyrolysis – Test method |
| ISO 18553:2002+Amd 1:2007 | Method for the assessment of the degree of pigment or carbon black dispersion in polyolefin pipes, fittings and compounds |
| ISO 9969:2016 | Thermoplastics pipes – Determination of ring stiffness |
| EN ISO 13263:2017 | Thermoplastics piping systems for non-pressure underground drainage and sewerage – Thermoplastics fittings – Test method for impact strength |

Excel Enbeam 2 Way External 18/14 mm Blowing Tube Green

Part Code: 208-787

sales@excel-networking.com
excel-networking.com

| | |
|------------------------------------|--|
| IEC 60304:1982 | Color code |
| ASTM D 1693:2015 | Standard Test Method for Environmental Stress Cracking of Ethylene Plastics |
| ISO 11357-6:2018 | Plastics – Differential scanning calorimetry (DSC) – Part 6: Determination of oxidation induction time (isothermal OIT) and oxidation induction temperature (dynamic OIT) |
| ČSN EN ISO 899-2:2003/A1:2015 | Plastics – Determination of creep behavior – Part 2: Flexural creep by three-point loading – Amendment 1 |
| IEC 60 794-3-20:2016 | Optical fibre cables – Part 3-20: Outdoor cables – Family specification for self-supporting aerial telecommunication cables |
| IEC 60794-4:2018 | Optical fibre cables – Part 4: Sectional specification – Aerial optical cables along electrical power lines |
| IEC 60 794-5:2014 | Optical fibre cables – Sectional specification – Microduct cabling for installation by blowing |
| Directive 2011/65/EU (RoHS II) | Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states). |
| Directive (EU) 2015/863 (RoHS III) | Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant. |
| Directive 2008/98/EC (WFD) | Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988). |
| ECHA SCIP Database | Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH. |
| Regulation (EU) 2019/1021 (POPs) | EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355). |
| UK SI 2012 No. 3032 | The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) |

Excel Enbeam 2 Way External 18/14 mm Blowing Tube Green

Part Code: 208-787

sales@excel-networking.com
excel-networking.com

Regulations 2019.

Part Code Table

| Part Code | Description |
|-----------|--|
| 208-786 | Excel Enbeam Single External 18/14 mm Blowing Tube Green |
| 208-787 | Excel Enbeam 2 Way External 18/14 mm Blowing Tube Green |
| 208-788 | Excel Enbeam 4 Way External 18/14 mm Blowing Tube Green |