


Excel Enbeam OM3 Multimode Blown Fibre EPFU 8 Fibre 50/125

Item Code: 208-817



- Available in OM3/OM4/OS2
- Bend Insensitive Fibres
- TIA-598-C Colour coded
- 25 Year system warranty
- Available in 4, 8 & 12-fibre bundles
- Easy strip
- Gel free Dielectric design

Product Overview

Enbeam Enhanced Performance Fibre Units (EPFU) are designed specifically for blown-fibre applications and are optimised for installation within our range of blown-fibre tubes. The fibres are contained within a soft acrylate layer which cushions the fibres. This layer is coated with a hard layer for strength and finally a low-friction coating to ensure low drag and maximise blowing distances within the tubes. The acrylate coatings are easy to remove to expose the 250-micron primary-coated fibres for quick splicing. The fibres are colour-coded according to TIA-598-C.

The fibre units are available in OM3, OM4 and OS2.

Product Specifications

Feature	Values
Number of Cores	8
Fibre type	Multi mode 50/125
Category	OM3
Outer sheath colour	Yellow
Outer diameter approx.	1.5 mm
Blown system	yes

Excel Enbeam OM3 Multimode Blown Fibre EPFU 8
Fibre 50/125

Item Code: 208-817



Part Number Table

Part Number	Description
208-816	Excel Enbeam OM3 Multimode Blown Fibre EPFU 4 Fibre 50/125
208-817	Excel Enbeam OM3 Multimode Blown Fibre EPFU 8 Fibre 50/125
208-818	Excel Enbeam OM3 Multimode Blown Fibre EPFU 12 Fibre 50/125

Excel is a world class premium performing end to end infrastructure solution designed,
Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.