Excel Enbeam Blown Fibre Tube Reducer 14 mm to 10 mm

Part Code: 208-844

sales@excel-networking.com
excel-networking.com

CIBSE TM65 Embodied Carbon: 0.254 kg CO2e



Main Features

/ Reducer

/ Locking clips included

/ CIBSE TM65 Embodied Carbon: 0.254 kg CO2e

/ Multiple sizes available

/ 25 Year system warranty

Product Overview

The Enbeam Push-Fit micro duct reducers are designed for use with the Enbeam blown fibre micro duct system and used to reduce the size of micro duct down to a smaller diameter tube as required. All push fit connectors are made from a clear transparent body, which gives the ability to visually inspect the installed cable and that the tubes are installed and aligned correctly.

Pre-installed locking clips are included on each end of the reducer to ensure tubes are locked into position ensuring a good connection is retained during the blowing process. Each connector can withstand up to 1 Joule of impact pressure and be reused if required. It is advisable to keep the connectors away from direct sunlight.

This data sheet was generated at 2:52pm 26th November 2026 and is subject to change at any time.

sales@excel-networking.com
excel-networking.com

Product Specifications

Feature	Values

Additional specifications

Features	Values	
Materials	**body**	**Clear polyamide**
	grip	
	cover	
	clips	
Pressure	**burst**	**25 bar**
	working	
Impact resistance		
UV Resistance		
Lifetime expectancy	**total**	**25 years**
Temperatures	**operating**	**-15°C to +45°C**
	installation	

Standards

Applicable standard	Detail
BS EN 50411-2-8:2009	Fibre organisers and closures to be used in optical fibre communication systems. Product specifications. Microduct connectors, for air blown optical fibres, Type 1
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in

This data sheet was generated at 2:52pm 26th November 2026 and is subject to change at any time.

	Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
UK SI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

Part Code Table

Part Code	Description
208-826	**Excel Enbeam Blown Fibre Tube Reducer 5 mm to 3 mm**
208-827	**Excel Enbeam Blown Fibre Tube Reducer 6 mm to 4 mm**
208-840	**Excel Enbeam Blown Fibre Tube Reducer 7 mm to 5 mm**
208-841	**Excel Enbeam Blown Fibre Tube Reducer 14 mm to 12 mm**
208-842	**Excel Enbeam Blown Fibre Tube Reducer 16 mm to 14 mm**
208-843	**Excel Enbeam Blown Fibre Tube Reducer 12 mm to 10 mm**
208-844	**Excel Enbeam Blown Fibre Tube Reducer 14 mm to 10 mm**

This data sheet was generated at 2:52pm 26th November 2026 and is subject to change at any time.

Excel Enbeam Blown Fibre Tube Reducer 14 mm to 10 mm

Part Code: 208-844

sales@excel-networking.com
excel-networking.com

This data sheet was generated at 2:52pm 26th November 2026 and is subject to change at any time.