

# Excel Enbeam Gas Block Connector 14 mm for use with 3-6 mm Micro Blown Cable

Part Code: 208-864

sales@excel-networking.com  
excel-networking.com



## Main Features

- / Gas block connector
- / Locking clips included
- / Multiple sizes available
- / 25-year Warranty

## Product Overview

The Enbeam Push-Fit micro duct gas block connectors are designed for use with the Enbeam blown fibre micro duct system. All push fit connectors are made from a clear transparent body, which gives the ability to visually inspect the installed cable and that the tubes are installed and aligned correctly.

Pre-installed locking clips are included on each end of the connector to ensure tubes are locked into position ensuring a good connection is retained during the blowing process. Each connector can withstand up to 1 Joule of impact pressure and be reused if required.

Suitable for cable diameters of 0.5 to 12 mm. It is advisable to keep the connectors away from direct sunlight.

# Excel Enbeam Gas Block Connector 14 mm for use with 3-6 mm Micro Blown Cable

Part Code: 208-864

sales@excel-networking.com  
excel-networking.com

## Product Specifications

Feature	Values
Model	Connector

## Additional specifications

Features		Values
Materials	<b>body</b>	<b>Transparent HP polymer</b>
	<b>grip</b>	<b>Stainless steel</b>
Gas/water seal		<b>&gt;0.5 bar</b>
Pressure	<b>burst</b>	<b>25 bar</b>
	<b>working</b>	<b>15 bar</b>
UV Resistance		<b>None</b>
Lifetime expectancy	<b>total</b>	<b>20 years</b>
Temperatures	<b>operating</b>	<b>-20 °C to +50 °C</b>
	<b>installation</b>	<b>-20 °C to +50 °C</b>

## Standards

Applicable standard	Detail
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.

# Excel Enbeam Gas Block Connector 14 mm for use with 3-6 mm Micro Blown Cable

Part Code: 208-864

sales@excel-networking.com  
excel-networking.com

Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
UK SI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

## Part Code Table

Part Code	Description
208-824	<b>Excel Enbeam Gas Block Connector 5mm for use with 0.5-3mm Micro Blown Cable</b>
208-864	<b>Excel Enbeam Gas Block Connector 14 mm for use with 3-6 mm Micro Blown Cable</b>
208-865	<b>Excel Enbeam Gas Block Connector 14 mm for use with 6-8 mm Micro Blown Cable</b>
208-866	<b>Excel Enbeam Gas Block Connector 14 mm for use with 8-10 mm Micro Blown Cable</b>
208-867	<b>Excel Enbeam Gas Block Connector 16 mm for use with 6-8 mm Micro Blown Cable</b>
208-868	<b>Excel Enbeam Gas Block Connector 16 mm for use with 8-10 mm Micro Blown Cable</b>
208-869	<b>Excel Enbeam Gas Block Connector 16 mm for use with 10-12 mm Micro Blown</b>

# Excel Enbeam Gas Block Connector 14 mm for use with 3-6 mm Micro Blown Cable



Part Code: 208-864

sales@excel-networking.com  
excel-networking.com

## Cable

---

