

Excel Enbeam Gas Block Connector 14mm for use with 6-8mm Micro Blown Cable

Item Code: 208-865



- ✕ Gas block connector
- ✕ Multiple sizes available
- ✕ Locking clips included
- ✕ 25-year Warranty

Product Overview

The Enbeam Push-Fit micro duct gas block connectors are designed for use with the Enbeam blown fibre micro duct system. All push fit connectors are made from a clear transparent body, which gives the ability to visually inspect the installed cable and that the tubes are installed and aligned correctly.

Pre-installed locking clips are included on each end of the connector to ensure tubes are locked into position ensuring a good connection is retained during the blowing process. Each connector can withstand up to 1 Joule of impact pressure and be reused if required.

Suitable for cable diameters of 0.5 to 12mm. It is advisable to keep the connectors away from direct sunlight.

Product Specifications

| Feature | Values |
|---------|-----------|
| Model | Connector |

Additional specifications

| Features | | Values |
|---------------------|---------|------------------------|
| Materials | body | Transparent HP polymer |
| | grip | Stainless steel |
| Gas/water seal | | >0.5 bar |
| Pressure | burst | 25 bar |
| | working | 15 bar |
| UV Resistance | | None |
| Lifetime expectancy | total | 20 years |

Excel Enbeam Gas Block Connector 14mm for use with 6-8mm Micro Blown Cable

Item Code: 208-865



| | | |
|--------------|--------------|------------------|
| Temperatures | operating | -20 °C to +50 °C |
| | installation | -20 °C to +50 °C |

Standards

| Applicable standard | Detail |
|--|---|
| RoHS-II/-III (2011/65/EU & 2015/863): 2023 | Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III). |
| WFD: 2023 | Compliant to Waste Framework Directive |
| SCIP: 2023 | Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products) |
| POPs (EU) No 2019/1021 | EU Regulation for the restriction of Persistent Organic Pollutants. |

Part Number Table

| Part Number | Description |
|-------------|--|
| 208-824 | Excel Enbeam Gas Block Connector 5mm for use with 0.5-3mm Micro Blown Cable |
| 208-864 | Excel Enbeam Gas Block Connector 14mm for use with 3-6mm Micro Blown Cable |
| 208-865 | Excel Enbeam Gas Block Connector 14mm for use with 6-8mm Micro Blown Cable |
| 208-866 | Excel Enbeam Gas Block Connector 14mm for use with 8-10mm Micro Blown Cable |
| 208-867 | Excel Enbeam Gas Block Connector 16mm for use with 6-8mm Micro Blown Cable |
| 208-868 | Excel Enbeam Gas Block Connector 16mm for use with 8-10mm Micro Blown Cable |
| 208-869 | Excel Enbeam Gas Block Connector 16mm for use with 10-12mm Micro Blown Cable |

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.