


# Excel Enbeam Divisible Gas Block Seal 5 mm for use with 1.65 mm Micro Blown Cable

Part Code: 208-872

sales@excel-networking.com  
excel-networking.com



## Main Features

/ Gas seal

/ Multiple sizes available

/ 25-year Warranty

## Product Overview

The Enbeam Push-Fit divisible gas seals are designed for use with the Enbeam blown fibre micro duct system.

The seals are designed to be fitted after cables have been blown into the micro duct and used to prevent gas and water entering or exiting the duct. The seal consists of two parts; the clear main body and a split rubber seal and can be used for cable diameters of 1.15mm to 3mm cable.

## Product Specifications

Feature	Values
---------	--------

# Excel Enbeam Divisible Gas Block Seal 5 mm for use with 1.65 mm Micro Blown Cable

Part Code: 208-872

sales@excel-networking.com  
excel-networking.com

Model

Gas block seal

## Additional specifications

Features		Values
Materials	body	Polycarbonate
	seal	Thermoplastic elastometers
Gas tightness		0.5 bar
Impact resistance		3J
UV Resistance		None
Lifetime expectancy	total	20 years
Temperatures	operating	-20°C to +60°C
	installation	-5°C to +50°C

## Standards

Applicable standard	Detail
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article

# Excel Enbeam Divisible Gas Block Seal 5 mm for use with 1.65 mm Micro Blown Cable

Part Code: 208-872

sales@excel-networking.com  
excel-networking.com

33(1). Submission obligations met under EU REACH and UK REACH.

Regulation (EU) 2019/1021 (POPs)

EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).

UK SI 2012 No. 3032

The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

## Part Code Table

Part Code	Description
208-870	Excel Enbeam Divisible Gas Block Seal 5 mm for use with 1.15 mm Micro Blown Cable
208-872	Excel Enbeam Divisible Gas Block Seal 5 mm for use with 1.65 mm Micro Blown Cable
208-873	Excel Enbeam Divisible Gas Block Seal 7 mm for use with 2.5 mm Micro Blown Cable