Item Code: 208-873







Product Overview

The Enbeam Push-Fit divisible gas seals are designed for use with the Enbeam blown fibre micro duct system.

The seals are designed to be fitted after cables have been blown into the micro duct and used to prevent gas and water entering or exiting the duct. The seal consists of two parts; the clear main body and a split rubber seal and can be used for cable diameters of 1.15mm to 3mm cable.

Product Specifications

Feature	Values
Model	Gas block seal

Additional specifications

Features		Values
Materials	body	Polycarbonate
	seal	Thermoplastic elastometers
Gas tightness		0.5 bar
Impact resistance		3J
UV Resistance		None
Lifetime expectancy	total	20 years
Temperatures	operating	-20°C to +60°C
	installation	-5°C to +50°C

Item Code: 208-873



Standards

Applicable standard	Detail
RoHS-II/-III (2011/65/EU & 2015/863): 2023	Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).
WFD: 2023	Compliant to Waste Framework Directive
SCIP: 2023	Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
POPs (EU) No 2019/1021	EU Regulation for the restriction of Persistent Organic Pollutants.

Part Number Table

Part Number	Description
208-870	Excel Enbeam Divisible Gas Block Seal 5mm for use with 1.15mm Micro Blown Cable
208-872	Excel Enbeam Divisible Gas Block Seal 5mm for use with 1.65mm Micro Blown Cable
208-873	Excel Enbeam Divisible Gas Block Seal 7mm for use with 2.5mm Micro Blown Cable

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.