

# Excel Enbeam 1x 16 Open-Ended PLC Splitter

Item Code: 208-903



Compact design

Low insertion loss

Operating wavelength from 1260 nm to 1650 nm

25 Year system warranty

CIBSE TM65 Embodied Carbon: 0.125 kg CO2e

## Product Overview

The Enbeam Planar Lightwave Circuit (PLC) Splitter is fabricated using silica optical waveguide technology. Its compact size, high reliability, wide operating wavelength and good channel-to-channel uniformity is widely used in Passive Optical Networks (PON).

Excel provides whole series of 1xN splitter products that are tailored for specific applications. All products meet GR-1209-CORE and GR-1221-CORE requirements.

## Product Specifications

| Feature  | Values          |
|----------|-----------------|
| Material | Metal (housing) |

## Additional specifications

| Features                   | All               | 1x4  | 1x8  | 1x16 | 1x32 |
|----------------------------|-------------------|------|------|------|------|
| Operating wavelength       | 1260 to 1650 nm   |      |      |      |      |
| Fibre type                 | G657A2            |      |      |      |      |
| Temperature stability (dB) | (-40 °C to 85 °C) | ≤0.4 | ≤0.4 | ≤0.5 | ≤0.5 |
| Storage temperature        | -40 °C to 85 °C   |      |      |      |      |
| Return loss                | ≥55 dB            |      |      |      |      |

# Excel Enbeam 1x 16 Open-Ended PLC Splitter



Item Code: 208-903

|                                |        |         |           |           |           |
|--------------------------------|--------|---------|-----------|-----------|-----------|
| Directivity                    | >55 dB |         |           |           |           |
| Wavelength dependent Loss (dB) |        | 0.3     | 0.3       | 0.3       | 0.5       |
| Insertion loss P/S Grade (dB)  |        | 7.2/7.4 | 10.3/10.7 | 13.5/13.7 | 16.5/16.9 |
| Maximum power handling         | 500 mW |         |           |           |           |

## Additional specifications

| Features                         | 1x4 | 1x8 | 1x16 | 1x32 |
|----------------------------------|-----|-----|------|------|
| Loss Uniformity (dB)             | 0.6 | 0.8 | 1    | 1.5  |
| Polarization Dependent Loss (dB) | 0.1 | 0.1 | 0.2  | 0.25 |

## Standards

| Applicable standard                | Detail  |
|------------------------------------|---|
| Directive 2011/65/EU (RoHS II)     | Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).                    |
| Directive (EU) 2015/863 (RoHS III) | Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.  |
| IEC 61754-1:2013                   | Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 1: General and guidance                                    |
| ISO/IEC 11801-1:2017               | Information technology - Generic cabling for customer premises: Part 1 General Requirements   |
| EN 50173-1:2018                    | Information technology. Generic cabling systems - General requirements  |
| Directive 2008/98/EC (WFD)         | Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).                          |
| ECHA SCIP Database                 | Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and |

# Excel Enbeam 1x 16 Open-Ended PLC Splitter



Item Code: 208-903

## UK REACH.

Regulation (EU) 2019/1021 (POPs)

EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).

UK SI 2012 No. 3032

The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

## Part Number Table

| Part Number | Description                                |
|-------------|--|
| 208-901     | Excel Enbeam 1x 4 Open-Ended PLC Splitter  |
| 208-902     | Excel Enbeam 1x 8 Open-Ended PLC Splitter  |
| 208-903     | Excel Enbeam 1x 16 Open-Ended PLC Splitter |
| 208-904     | Excel Enbeam 1x 32 Open-Ended PLC Splitter |

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at [sales@excel-networking.com](mailto:sales@excel-networking.com)



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.