


Excel 24AWG 4 Core Belden Alternative Multicore Cable SCR LSF Eca Type 9534 500 m Grey

Item Code: 2404COFV-EX500



✕ CIBSE TM65 Embodied Carbon: 116.554 kg CO2e

Product Overview

Excel Multicore cables manufactured and designed for sound broadcast, audio and instrumentation offering an alternative Belden style cable, with tinned copper conductors. A four core cable with 24 AWG size conductors, single Drain Wire and overall foil shield in an LSF Grey Sheath rated as Euroclass Eca.

Product Specifications

Feature	Values
Diameter of conductor	TC 0.20 ±0.008 x 7
Total number of cores	4
Core identification	black, White, Red, Green
Overall screening	Foil
Outer sheath material	LSZH
Outer sheath colour	Grey
Flame retardant according to IEC 60332-1-2	yes
Halogen free (acc. IEC 60754-2)	yes
Reaction-to-fire class according to EN 13501-6	Eca
Outer diameter approx.	4.60mm ± 0.2
Min. permitted bending radius, stationary application/permanent installation	40 mm
Operating Temperature Range	-20...70 °C
Category	Multicore Overall Screened



Part Number Table

Part Number	Description
2404COFV-EX500	Excel 24AWG 4C M/Core LSF Eca Type 9534 500m G

Excel is a world class premium performing end to end infrastructure solution designed,
Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.