

Excel Enbeam OS2 Drop Cable Tight Buffered  
G.657.A2 4mm 4 Core 9/125 Cca White

Item Code: 275-104



- ✕ Suitable for internal
- ✕ G.657.A2
- ✕ LSZH
- ✕ Euro class Cca-s1,d1,a1

Product Overview

Enbeam 4 fibre drop cable has been designed for internal installations aimed at the FTTH and multi dwelling market. The cable consists of a single core 900um tight buffer single mode G.657.A2 fibre surrounded by a micro module and aramid yarn as a strength member covered with a white LSZH outer sheath.

Product Specifications

Feature	Values
Number of Cores	4
Type of tube	Tight
Fibre type	Single mode 9/125
Category	OS2
Rodent resistant	no
Outer sheath colour	White
Flame retardant according to IEC 60332-1-2	yes
Low smoke (acc. IEC 61034-2)	yes
Reaction-to-fire class according to EN 13501-6	Cca
Smoke development class according to EN 13501-6	s1a
Euro class flaming droplets/particles according to EN 13501-6	d1
Euro class acidity according to EN 13501-6	a2
Outer diameter approx.	4 mm

Excel Enbeam OS2 Drop Cable Tight Buffered  
G.657.A2 4mm 4 Core 9/125 Cca White

Item Code: 275-104



Part Number Table

Part Number	Description
275-104	Excel Enbeam OS2 Drop Cable Tight Buffered G.657.A2 4mm 4 Core 9/125 Cca White

Excel is a world class premium performing end to end infrastructure solution designed,  
Manufactured, supported and delivered without compromise.

Contact us at [sales@excel-networking.com](mailto:sales@excel-networking.com)



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.