
Item Code: 328-012









X G.657.A1 Bend insensitive
X Rodent resistant
X Ultra-Light Weight Design
X 7 mm cable diameter
X Euroclass Fca
X PIA Approved
X CIBSE TM65 Embodied Carbon: 0.218 kg CO2e

Product Overview

Enbeam OS2 Ultra-Light Weight SM G.657.A1 Aerial Fibre Cable Loose Tube 12 Core 9/125 HDPE Fca Black, part of a huge range of OS2 Fibre optic cables fully stocked at Mayflex.

The Enbeam Ultra-Light Weight fibre has been designed for aerial installations into the fibre access network.

The cable is constructed from multiple gel filled micromodules, overlaid with water swellable yarn and water blocking tape and then covered with a High Density Polyethylene (HDPE) outer jacket with yellow stripes containing 2 brass coated steel wire strength members and offers 4 to 48 fibre core counts.

Product Specifications

Values	
12	
Loose tube	
12	
Single mode 9/125	
OS2	
HDPE	
Black	
	Loose tube 12 Single mode 9/125 OS2 HDPE

Item Code: 328-012



Reaction-to-fire class according to EN 13501-6

Fca

Outer diameter approx.

7 mm

Product drawing



Item Code: 328-012







For fibre core counts above 12 the colour sequence is repeated with the addition of a mark every 70mm for cores 13-24 and two marks for 25-36 and so on.

Fibre specifications

Features		Values
Attenuation	@1310nm	≤0.35 dB/km
	@1550nm	≤0.21 dB/km
	@1625nm	≤0.23 dB/km
Chromatic dispersion coefficient	1285nm - 1330nm	≤3.5ps/km·nm
	@1550nm	≤18.0ps/km·nm
	1565nm - 1625nm	≤22.0ps/km·nm
Zero dispersion wavelength - $\lambda 0$		1302-1324nm
Zero dispersion slope		≤0.092 ps/(km·nm2)
Cut-off Wavelength - λcc		1100-1320nm
Polarization mode dispersion	Individual fibre	≤0.1ps/√Km
	Design link value	≤0.04ps/√Km
Macro bending loss	100 turns, 50mm radius	≤0.05dB@1310/1550nm
	100 turns, 60mm radius	≤0.05dB@1625nm
Cladding diameter		125.0±0.7μm
Cladding non-circularity		≤1.0%
Primary coating diameter		242±5μm
Primary coating material		UV Cured Acrylite
Core - Cladding concentricity error		≤0.5µm
Coating - Cladding concentricity error		≤12μm
Fibre curl radius		≥4m

Item Code: 328-012



	@1550 nm	10.4±0.5μm
Proof stress level		1.0% (100kpsi)

Cable specifications

Features		Values
Weight (kg/km)	4-48 core	40.0 (nominal)
Number of fillers	4-12 core	2
	24-core	1
	36-48 core	0
Embedding strength member	Dimension	3 x 0.32 mm
	Туре	Brass Coated Steel Wire
Moisture Barrier	Туре	Water Blocking Yarn & Water Swellable Tape
Outer sheath	Material	HDPE
	Thickness	1.6 mm (nominal)
	Strip marking width	1.25 mm (nominal)
	Strip marking type	HDPE Yellow
Break load		1900 N
Tensile Strength		1250 N
Crush Resistance		2000 N
Minimum Bending Radius	During installation	20D
	After installation	10D
Voltage Test	Along power line, min vertical distance of 1.8 m	11 Kv
Resistance to wind/ice	97 kph wind	No ice
	80 kph wind	5 mm ice
	0 kph wind	10 mm ice
Temperature	Installation	-10°C to +60°C
	Operation	-30°C to +70°C
	Storage	-40°C to +70°C

Item Code: 328-012



Standards

Applicable standard	Subject
IEC 60332-1-2:2004	Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for $\bf 1$ kW pre-mixed flame
IEC 60754-2:2014+A1:2020	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity
IEC 61034-2:2005+A2:2020	Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements
IEC 60793-1-1:2022	Optical fibres - Part 1-1: Measurement methods and test procedures - General and guidance
IEC 60793-1-20:2014	Optical fibres - Part 1-20: Measurement methods and test procedures - Fibre geometry
IEC 60793-1-21:2001	Optical fibres - Part 1-21: Measurement methods and test procedures - Coating geometry
IEC 60793-1-22:2001	Optical fibres - Part 1-22: Measurement methods and test procedures - Length measurement
IEC 60793-1-30:2010	Optical fibres - Part 1-30: Measurement methods and test procedures - Fibre proof test
ΠU G.652.D	Characteristics of a single-mode optical fibre and cable
ITU-T G.657	Characteristics of a bending-loss insensitive single-mode optical fibre and cable
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
EN 50575: 2014 + A1: 2016	Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements
EN 50399:2011+A1:2016	Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
ANSI/TIA 568-3.D	Optical Fiber Cabling and Components Standard
ANSI/TIA/EIA 598-D	Optical Fibre Cable Colour Coding
RoHS-II/-III (2011/65/EU & 2015/863): 2023	Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).

Item Code: 328-012



WFD: 2023	Compliant to Waste Framework Directive
SCIP: 2023	Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
POPs (EU) No 2019/1021	EU Regulation for the restriction of Persistent Organic Pollutants.

Part Number Table

Part Number	Description
328-012	Excel Enbeam OS2 ULW Rodent Resistant G.657.A1 Aerial Fibre Cable LT 12 Core Fca Black

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.